



This form is ONLY for corners filed under the 2015 State Survey and Remonumentation Grant Agreement
Filing Requirement: MCL 54 268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2015 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Newaygo County common to Mecosta County Goodwell Township common to Mecosta Township

Corner Type	Survey Township	Corner Code
Original Public Land Survey Corner	T 14N R 11W	M-07
• MCL 54.202(g)	T 14N R 10W	A-07
• MCL 54.262(g)	T R	
	T R	
Property Controlling Corner	T R	
• MCL 54.202(i)	T R	
• MCL 54.262(h)	T R	
• MCL 54.262(i)	T R	
Protracted Public Land Survey Corner	T R	
• MCL 54.202(k)	T R	
• MCL 54.262(i)	T R	

Section Corner common to Sections 13 and 24, T14N R11W, Goodwell Township, Newaygo County, common to Section Corner common to Sections 18 and 19, T14N R10W, Mecosta Township, Mecosta County, Michigan.

Part A: Corner(s) History

079

John Hodason, September 5, 1837

Set post corner

#1 20" Beech S36°W 21 links (13.86")

#2 26" Maple N43°W 9 links (5.94')

Newaygo County Road Commission Sheet
1950's±

Well point and stone

#3 Power Pole S50°W 85.5'

#4 Corner Post N45°W 44.5'

Norman L. Ochs, R.L.S. # 22439

LCRC recorded in Liber 1, page 445

Found well point and stone raised with 3/4" Pipe

#5 16" White Oak S50°E 34 6"

#3 Power Pole S50°W 85.65'

#6 8" Walnut N55°W 117.62'

John E. McLane, R.L.S. #28418

Survey recorded in Liber 13, Pages 60-62 October 1, 2004
Shows a distance of 2738.14' to the North ¼ Corner, Section 19.

Lyman June, County Surveyor Mecosta Co.
Field notes recorded in Book 1, page 94 November 5 & 6, 1902
Stake shows distance of 41.34 chains (2728.44') to North ¼ Corner
and 40.10 chains (2646.66') to West ¼ Corner Section 19.

Patrick A. Salisbury, R.L.S. #13594

Drawing No 73153Ac September 27, 1973

Found well point and stone raised with $\frac{3}{4}$ " Pipe

#5 16" White Oak S50°E 34.6"

#3 Power Pole S50°W 85.65'

#6 8" Walnut N55°W 117.62'

William G. Tingley, R.L.S. # 30104

LCRC recorded in Liber 2, Page 367 December 31, 1990
Found 1" Iron Pipe — location of centerline "X" North-South-West
gravel roads.

#7 10" Oak S45°W 55.57' set nail in East side

#8 20" Twin Pine N20°W 76.95' set nail in East side

#5 20" Maple S45°E 34.62' found nail in North side

#9 6" Cherrv N88°E 16.50'

