

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner(s)

E-6, Being the $\frac{1}{4}$ corner common to Sections 16 and 17, T22N, R12W.
Found Wexford County aluminum monument in centerline of N-S road, 62' North of trail to the West and on center of trail to the East. Line E-6 to E-5 fits the West line of the Plat of Doruise Airport Estates Subdivision. Fits single proportion position E-6 to E-5 well. Accepted Wexford County aluminum monument as a careful and faithful reestablishment of the position of the original corner. Replaced Wexford County aluminum monument with 5/8" x 36" iron with Wexford County brass cap.

Distance to E-5, 2647.61'-Grid; 2640.0'-GLO; 2647.68'-WT; 2647.39'-JAR
Distance to E-7, 2647.46'-Grid; 2640.0'-GLO; 2647.68'-WT

Part C: Field Evidence of Perpetuation or Monumentation of Corner(s)

E-6, Being the $\frac{1}{4}$ corner common to Sections 16 and 17, T22N, R12W.

Set 5/8" x 36" iron with Wexford County brass cap, stamped 2015, 16 & 17, JAR, 25869

S81°E 79.90' 12" Red Pine (5)
S43°E 48.70' 12" Red Pine (4)
S22°E 78.20' 17" Red Pine (7)
N43°E 27.27' 16" Poplar

L: 8 P: 223 201500006853
COR Fee: \$ 17.00
11/19/2015 09:59 AM Page: 2 of 2

Lorie L. Sorensen

Register of Deeds - Wexford County, MI



Date of Observation	Latitude	Longitude	Datum and Adjustment Year	Epoch Date
September 24, 2015	N 44°18'07.13"	W 85°46'51.48"	NAD83 (2011)	2010.00

Method: GPS Network real-time position survey to MDOT CORS.


Disclaimer: The Latitude and Longitude reported hereon was observed using global positioning methods with an estimated positional accuracy of 1 foot, more or less, reported at time of observation. The reported Latitude and Longitude is a navigational accessory to the approximate corner location and shall not be used to reestablish the corner position or used in establishing property boundaries.

I, James A. Ray, in a field survey on August 10, 2015, certify under the requirements of the State Survey and Remonumentation Act, 1990 PA 345, MCL 54.261 to 54.279, and the Corner Recordation Act, 1970 PA 74, MCL 54.201 to 54.210d, that the corner(s) identified and described hereon has been perpetuated or monumented as described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan.

James A. Ray

Professional Surveyor's License No.: 25869

Axin Land Surveys, Inc., 811 Sunnyside Drive, Cadillac, MI 49601



Date: 10/09/2015

I, Craig J. Pullen, state that the corner(s) identified and described hereon and perpetuated or monumented as described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on 10/09/2015 and is accepted for filing in the Wexford County Remonumentation Program.

Craig J. Pullen

Professional Surveyor's License No.: 39095

Date

11-13-15