

Received
PRESQUE ISLE COUNTY
01-09-2015 09:11 am.

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

<u>Presque Isle</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>33N</u> R <u>5E</u>	<u>G-10</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Instrument 201500000109 OR Liber 558 Page 971

201500000109
Filed for Record in
PRESQUE ISLE COUNTY
CATHY I. IDALSKI, REG OF DEEDS
01-09-2015 At 09:21 am.
LC-REMON 17.00
OR Liber 558 Page 971 - 972


Register of Deeds Stamp & Figure Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Travis L. Horrocks, in a field survey on June 10, 2014 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.



A. Description of original monument and accessories and/or subsequent restoration:

G-10
SEE BACK


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-10
SET 1/2" ROD & REMON CAP #59298
ONLINE BETWEEN G-9 & G-11 AT GLO DISTANCE FROM THE GLO NOTE
CALL FOR ENTER SWAMP OF 2.39 CH (157.74') SOUTH OF CORNER.
EDGE OF SWAMP VERY DEFINED. 100' NORTH OF E-W FENCE LINE.
POSITION ALSO COINCIDES WITH SINGLE PROPORTIONAL
MEASUREMENT POSITION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-10
1/2" ROD & REMON CAP #59298
100' NORTH OF E-W FENCE
N 75° E 22.15' 24" MAPLE #59298
S 50° E 34.00' 12" MAPLE #59298
S 65° W 25.41' 12" MAPLE #59298
N 55° W 15.45' 8" MAPLE #59298

Redified by Peer Group
in accordance with P.A. 345
Chairman [Signature]
Date 11-4-2014



Signed by [Signature]
Surveyor's Michigan License No. 59298

WITNESS TAGS & NAILS USED

Date 11/06/14