

73°  
ORIGINAL

# FIELD NOTES

OF THE QUARTER OF THE

INDEPENDENT RESERVE

OF THE

SUBDIVISIONAL TIER

02

TOWNSHIP 24 NORTH, RANGE 6 EAST.

Of the Michigan Meridian,

In the State of Michigan.

EXECUTED BY

GEORGE R. YOUNG, U. S. Geological Engineer.

Assisted by

WILLIS F. BAUDY, U. S. Surveyor.

In the capacity of U. S. Surveyor, under Special Instructions dated May 13, 1927,  
Associate Supervisor of Surveys  
Issued by the Chief-States-Surveyor-General to govern surveys included in Group

14, which were approved by the Commissioner of the General Land  
Office, May 24, 1927, and designations Instructions dated May 25, 1927.

Survey commenced June 3, 1927.

Survey completed August 23, 1927.



2100/415

# INDEX DIAGRAM.

Township 24 NORTH Range 6 EAST.

60	59	58	57	56	55
54	53	52	51	50	49
48	47	46	45	44	43
42	41	40	39	38	37
36	35	34	33	32	31
30	29	28	27	26	25
24	23	22	21	20	19
18	17	16	15	14	13
12	11	10	9	8	7
6	5	4	3	2	1

For info. on N-E & W line see  
 Her Dep Assn's T 24 N R 6 E  
 Book of Book

500 4 3 2 1

Dependent Reserve of the Subdivisional Lines,  
 S. 24 N., R. 6 E., Michigan Meridian, Michigan.

Dependent Reserve of the Subdivisional Lines of  
 S. 24 N., R. 6 E., Michigan Meridian, Michigan,  
 Surveyed in 1845 by James H. Bullett, D. S.

Survey commenced June 5, 1927 and executed with Part

Solar Transits Nos. 16728 and 16729. For description  
 and text of instruments, see Field Notes of Dependent  
 Reserve of the North, East and West Boundaries of  
 S. 24 N., R. 6 E., and the East and North Boundaries  
 of S. 24 N., R. 7 E., Michigan Meridian, Michigan,  
 executed by Guy R. Veal, U. S. Cadastral Engineer,  
 assisted by Willis W. Bandy, U. S. Surveyor, in 1927.

I commence at the cor. of secs. 1, 2, 35 and 36, on the  
 S. W. of the township, which is an iron post, 2 ins.  
 diam., 9 ins. above ground, firmly set with brass cap  
 marked, and witnessed as described in the official

S. 0° 46' N., 49 1/4' W. line: bet. sec. 35 and 36.

Other Tenth land, through timber and light, water growth  
 Proportional distance.

Set an iron post, 3/4" dia., 1 in. above ground, in  
 the ground, top established 1/4" sec. cor. of sec. 35  
 and 36, with brass cap mkt.

From which I and I, Sec. 1, 1927, from cor. of sec. 35  
 1 year pine, 5 ins. diam., bears S. 67° 30' E., 35 lbs.  
 dist., mkt. 1/4" S 35 R E.

A black oak, 8 ins. diam., bears S. 64° 30' W., 14  
 lbs. dist., mkt. 1/4" S 35 R E.

Head, bears S. 70° W. and S. 70° E.  
 Proportional distance.

Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in  
 the ground, for reestablished cor. of sec. 25, 26,  
 35 and 36, with brass tablet mkt.

ould Nits . . . 215 . all 12



Dependent Recovery of the Subdivisional Lines,  
E. 24 N., R. 6 E.

Chain  
 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

1. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

2. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

3. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

4. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

5. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

6. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

7. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

8. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

9. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

10. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

11. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

12. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

13. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

14. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

15. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

16. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

17. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

18. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

19. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

20. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

21. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

22. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

23. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

24. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

25. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

26. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

27. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

28. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

29. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

30. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

31. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

32. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

33. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

34. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

35. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

36. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

37. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

38. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

39. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

40. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

41. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

42. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

43. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

44. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

45. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

46. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

47. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

48. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

49. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

50. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

51. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E. 24 N. 6 E.  
 S 26 S 25 S 25 S 25  
 S 35 S 36

Dependent Recovery of the Subdivisional Lines,  
E. 24 N., R. 6 E.

A cedar stump, 10 ins. diam., bears S. 40° W.,  
 49 lbs. dist., with blaze.

A birch, 5 ins. diam., bears N. 39° E., 17 lbs.  
 dist., and 1/4 S 25° B T.

A cedar, 6 ins. diam., bears S. 33° 30' E., 30 lbs.  
 dist., and 1/4 S 36° B T.

Blaze

N. 69° 04' E., on a true line, bet. sees. 25 and 36 (E-3)  
 foot of descent, bears N. 30° W. and S. 30° E.

Enter cedar and poplar swamp.

Enter flowage of Cooke Basin, bears N. 60° W. and  
 S. 60° E.

Leave flowage, bears N. and S. Enter cedar swamp.

The cor. of sees. 25, 30, 31 and 36, on the E. bdy. of  
 the township, previously described.

Land, level and hilly.

Soil, sandy, 3rd rate, on upland; snuk, 3rd rate,  
 in swamp.

Timber, jack pine, cedar, black oak, poplar, tamarack.  
 Undergrowth, young timber and alder.

From the cor. of sees. 25, 26, 35 and 36  
 N. 0° 07' E., on a true line, bet. sees. 25 and 26.  
 Over level land, through scattering timber.

Over level land, through dense young poplar and  
 birch timber, and undergrowth.

Begin ascent of 100 feet over steep N. slope.

The S. shore of flowage of Cooke Basin on the Au Sable  
 River, bears E. and W. Thence over the waters of  
 Cooke Basin by triangulation.

The N. shore of flowage of Cooke Basin, bears E. and W.  
 Thence over level land, through dense young poplar and  
 birch timber, and undergrowth.

Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
 the ground, for reestablished 1/4 sec. cor. of sees.  
 25 and 26, with brass cap and



Dependent Reserve of the Subdivisional Lines,  
R. 24 N., R. 6 E.

4

- Chains
- 1/4 sec. 25  
S 26 | S 25  
1927
- From which  
A poplar, 4 ins. diam., bears N. 58° E., 10 lbs.  
dist., nhd. 1/4 S 25 B E.  
A poplar, 4 ins. diam., bears S. 70° W., 11 lbs.  
dist., nhd. 1/4 S 26 B E.
- 73.00 Inter cedar and tamarack swamp, bears E. and W.  
61.06 The true point for the cor. of secs. 23, 24, 25 and 26, which is marked by a wooden post, 4 x 4 x 30 ins. above ground, set by engineers of the Consumers Power Company from original bearing trees, about 1909. In place of the wooden post, set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for reestablished cor. of secs. 23, 24, 25 and 26, with brass cap nhd.
- From which  
A cedar, 12 ins. diam., bears S. 23° E., 31 lbs.  
dist., nhd. R 6 E S 25.  
And the remains of local bearing trees  
A cedar stump, 10 ins. diam., bears N. 17° 30' E., 13 lbs. dist., nhd. N E R S 24.  
A cedar stump, 12 ins. diam., bears S. 75° W., 34 lbs. dist., nhd. N E R.  
And new bearing trees  
A cedar, 12 ins. diam., bears N. 48° 30' E., 33 lbs.  
dist., nhd. R 24 N R 6 E S 24 B E.  
A cedar, 10 ins. diam., bears S. 60° E., 26 lbs.  
dist., nhd. R 24 N R 6 E S 25 B E.  
A spruce, 5 ins. diam., bears S. 81° 30' W., 20 lbs.  
dist., nhd. R 24 N R 6 E S 26 B E.  
A cedar, 10 ins. diam., bears N. 36° 45' W., 17 lbs.  
dist., nhd. R 24 N R 6 E S 25 B E.

Dependent Reserve of the Subdivisional Lines,  
R. 24 N., R. 6 E.

5

- Gaine Land, level and hilly.  
Soil, sandy, 3rd rate, on upland; muck, 3rd rate, in swamp.  
Timber, poplar, birch, cedar, tamarack, jack pine and spruce.  
Undergrowth, young timber and alder.
- S. 89° 32' E., on a true line, bet. secs. 24 and 25.  
Over level land, through cedar and tamarack swamp.
- 11.40 Leave swamp, bears DE. and SW. Thence over low, level land, through young poplar timber and undergrowth.
- 20.50 To higher, level land, bears N. and S.  
Proportional distance.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 24 and 25, with brass cap nhd.
- From which  
A poplar, 4 ins. diam., bears N. 12° E., 25 lbs.  
dist., nhd. 1/4 S 24 B E.  
A poplar, 10 ins. diam., bears S. 65° 45' E., 101 lbs. dist., nhd. 1/4 S 25 B E.
- 80.02 The cor. of secs. 19, 24, 25 and 30, on the E. Mtg. of the township, previously described.  
Land, level.  
Soil, muck, 3rd rate, in swamp; sandy, 3rd rate, elsewhere.  
Timber, poplar, birch, cedar, tamarack.  
Undergrowth, young timber and willow.
- From the cor. of secs. 25, 24, 25 and 26.  
N. 0° 12' W., on a true line, bet. secs. 23 and 24 (S. 8)  
Over level land, through cedar and tamarack swamp.  
24.90 A stream, 4 ins. wide, 6 ins. deep, course SE.  
40.12 The true point for the 1/4 sec. cor. of secs. 23 and 24, which is marked by a wooden post, 4 x 4 x 30 ins.



Dependent Recovery of the Subdivisional Lines, etc.  
R. 24 N., R. 6 S.

above ground, with an old, rotten wooden post on the ground at foot of post. The engineers of the Consumers Power Company report that they found the original corner post, about 1909.

In place of the wooden post, a corner has been set an iron post, 3 ft. long, 1 in. diam., 27 ins. in

the ground, for reestablished 1/4 sec. cor. of secs. 23 and 24, with brass cap nkt.

Level level above ground, 1/4 in. diam., brass cap nkt. 04.11

From which  
1927 Level, within 100 ft. of  
The remains of local bearing trees

A tamarack stump, 12 ins. diam., bears S. 20° 30' E., 86 lbs. dist., nkt. N R E.

A white pine stump, 20 ins. diam., bears N. 88° 30' W., 121 lbs. dist., nkt. N R E.

And new bearing trees

A tamarack, 6 ins. diam., bears S. 6° W., 58 lbs. dist., nkt. 1/4 S 24 B F.

A tamarack, 5 ins. diam., bears N. 20° 15' W., 20 lbs. dist., nkt. 1/4 S 23 B F.

Thence  
0-0-55' W., on a true line, bet. sec. 23 and 24 (R. 1)

Contains through dense tamarack swamp.  
22.00 Leave swamp, bears NE. and SW. Thence over gently rolling land, through scattering timber, out

39.68 The true point for the cor. of secs. 13, 14, 23 and 24, which is marked by a wooden post, 4 x 4 x 20 ins. above ground, set about 1909 by engineers of the Consumers Power Company through the original bearing

tree, as shown by their records.

Free, as shown by their records.

In place of the wooden post

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for reestablished cor. of secs. 13, 14, 23 and 24, with brass cap nkt.

15 Area covered to the true point for the cor. of secs. 13, 14, 23 and 24, with brass cap nkt. 51.04

Dependent Recovery of the Subdivisional Lines,  
R. 24 N., R. 6 S.

124 lbs. dist., nkt. S 14 N R E.

Local bearing trees  
9' oak jack-pine, 9' oak stump; bears N. 10° 30' W., 129 lbs. dist., with no marks.

129 lbs. dist., with no marks.

And new bearing trees

A jack pine, 10 ins. diam., bears N. 35° E., 141 lbs. dist., nkt. R 24 N R 6 S 13 B F.

A black oak, 8 ins. diam., bears S. 74° 30' E., 72 lbs. dist., nkt. R 24 N R 6 S 24 B F.

A jack pine, 8 ins. diam., bears S. 66° 45' W., 231 lbs. dist., nkt. S 24 B R 6 S 23 B F.

A jack pine, 9 ins. diam., bears N. 88° 45' W., 185 lbs. dist., nkt. R 24 N R 6 E S 14 B F.

Land, level and gently rolling.

Soil, mod. 3rd rate, fir swamp; sandy, 3rd rate, on upland.

Timber, tamarack, cedar, jack pine, poplar, black oak. Undergrowth, young timber, willow and alder.

5, 89° 47' E., on a true line; bet. sec. 13 and 24.

Over level land, through scattering timber.

26.00 Enter cedar and tamarack swamp; bears NE. and SW. 10.40

40.40 The true point for the cor. of secs. 13, 14, 23 and 24, which is marked by a wooden post, 3 ft. long, 2 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 13 and 24, with brass cap nkt.

Free, as shown by their records.

In place of the wooden post

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for reestablished cor. of secs. 13, 14, 23 and 24, with brass cap nkt.

12 Area covered to the true point for the cor. of secs. 13, 14, 23 and 24, with brass cap nkt. 51.04



69.50  
 Creek, 10 lbs. wide, 6 ins. deep, course SE.

80.80  
 The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the township, previously described.

Land, level.  
 Soil, sandy, 3rd rate, on upland; maple, 3rd rate, in swamp.  
 Timber, cedar, tamarack, jack pine, black oak, spruce. Undergrowth, young timber, willow and alder.

From the cor. of secs. 13, 14, 23 and 24.  
 N. 0° 43' E., on a true line, bet. secs. 13 and 14.  
 Over gently rolling land, through scattering timber. Thence over nearly level land.

15.00  
 Thence over nearly level land.

40.17  
 Proportional distance.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 13 and 14, with brass cap and.

1/4  
 S 13  
 1927

From which  
 A jack pine, 6 ins. diam., bears N. 27° 15' E., 127 lbs. dist., and 1/4 S 13 E T.

15  
 On a true line, bears S. 42° W., 230 lbs. dist., and 1/4 S 13 E T.

80.34  
 Proportional distance.  
 Set a concrete monument, 6 x 6 x 24 ins. in the ground, for reestablished cor. of secs. 11, 12, 13 and 14, with brass tablet and.

24 N. 6 E. 105 lbs. T.  
 S 11 12 15 lbs. T.  
 S 14 S 13

From which  
 A jack pine, 10 ins. diam., bears N. 19° E., 137 lbs. dist., and 24 N 6 E S 12 E T.  
 A jack pine, 10 ins. diam., bears S. 64° 30' E., 165 lbs. dist., and 24 N 6 E S 13 E T.  
 A jack pine, 8 ins. diam., bears S. 49° W., 51 lbs. dist., and 24 N 6 E S 14 E T.

61.00  
 A jack pine, 10 ins. diam., bears N. 86° W., 90 lbs. dist., and 24 N 6 E S 11 E T.

Land, gently rolling and level.  
 Soil, sandy, 3rd rate.  
 Timber, jack pine and black oak.

S. 89° 46' E., on a true line, bet. secs. 12 and 13.  
 Over level land, through timber and light undergrowth.

40.08  
 Proportional distance.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 12 and 13, with brass cap and.

1/4  
 S 12  
 1927

From which  
 A jack pine, 12 ins. diam., bears N. 2° 30' W., 52 lbs. dist., and 1/4 S 12 E T.

A jack pine, 8 ins. diam., bears S. 60° 45' E., 34 lbs. dist., and 1/4 S 13 E T.

50.00  
 Thence over gently rolling land.

61.80  
 On a true line, bears N. and S.

80.16  
 The cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the township, previously described.  
 Land, level and gently rolling.  
 Soil, sandy, 3rd rate.  
 Timber, jack pine and black oak. Undergrowth, young timber.

From the cor. of secs. 11, 12, 13 and 14.  
 N. 0° 23' E., on a true line, bet. secs. 11 and 12.  
 Over level land, through scattering timber.

16.80  
 Road, bears E. and W.

40.16  
 Proportional distance.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 11 and 12, with brass cap and.

1/4  
 S 11 S 12  
 1927



Dependent Recovery of the Subdivisional Lines,  
S. 24 N., R. 6 E.

From which  
A jack pine, 8 ins. diam., bears S. 17° 30' E.,  
20 lbs. dist., nhd. 1/4 S 12 R 7.  
A jack pine, 9 ins. diam., bears N. 69° 30' W.,  
6 lbs. dist., nhd. 1/4 S 11 R 7.  
The true point for the cor. of sec. 1, 2, 11 and 12,  
which is marked by a fallen wooden post, 3 x 3 x 24  
inches, set from original bearing trees by a local  
surveyor, apparently about 25 years ago.  
In place of the wooden post, set from sec. 1, 2,  
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
the ground, for reestablished cor. of secs. 1, 2, 11  
and 12, with brass cap nhd.

S 2	R 6
S 1	R 6
S 11	R 12

From which  
The remaining of original bearing trees  
A fallen and rotted Norway pine, bears S. 70° W.,  
131 lbs. dist.  
A fallen jack pine, 10 ins. diam., bears N. 71° E.,  
39 lbs. dist. (reced, N. 44° E., 39 lbs.)  
And local bearing trees  
A fallen jack pine, 12 ins. diam., bears N. 72° E.,  
136 lbs. dist., nhd. N E R.  
A jack pine, 9 ins. diam., bears S. 2° 30' W.,  
150 lbs. dist., nhd. N E R.  
And bear bearing trees  
A jack pine, 6 ins. diam., bears N. 72° E., 75 lbs.  
dist., nhd. 24 N R 6 S 1 R 7.  
A jack pine, 9 ins. diam., bears S. 25° E., 108 lbs.  
dist., nhd. 24 N R 6 S 12 R 7.  
A jack pine, 8 ins. diam., bears S. 35° 15' W., 33  
lbs. dist., nhd. 24 N R 6 S 11 R 7.  
A Norway pine, 15 ins. diam., bears N. 26° 15' W.,  
210 lbs. dist., nhd. 24 N R 6 S 2 R 7.  
Land, level.  
Soil, sandy, 3rd rate.  
Timber, jack pine and black oak.

Dependent Recovery of the Subdivisional Lines,  
S. 24 N., R. 6 E.

From which  
A Norway pine, 24 ins. diam., bears N. 21° 23' W.,  
325 lbs. dist., nhd. 1/4 S 1 R 7.  
A jack pine, 8 ins. diam., bears S. 6° 30' W.,  
25 lbs. dist., nhd. 1/4 S 12 R 7.  
A local corner, A wooden post, 4 x 4 x 24 ins., bears  
S. 19° W., 23 lbs. dist. This corner apparently was  
set by proportional measurement. The local corner  
was not the east boundary of secs. 1 and 12 would not  
be accepted, and this one was therefore unacceptable.  
The cor. of secs. 1, 6, 7 and 12, on the N. half, of the  
township, previously described.  
Land, level.  
Soil, sandy, 3rd rate.  
Timber, jack pine and black oak.  
From the cor. of secs. 1, 2, 11 and 12,  
S. 0° 08' E., on a true line, bet. secs. 1 and 2.  
Over level land, through scattering timber.  
Proportional distances.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for reestablished 1/4 sec. cor. of secs.  
1 and 2, with brass cap nhd.

1/4	S 1
3/4	S 1

From which  
A jack pine, 6 ins. diam., bears S. 61° E.,  
89 lbs. dist., nhd. 1/4 S 1 R 7.  
A jack pine, 12 ins. diam., bears S. 6° E.,  
170 lbs. dist., nhd. 1/4 S 2 R 7.



Chains  
54.00 Road, bears NE. and SW.  
74.65 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the township, previously described.  
21 Land, Level.  
Soil, sandy, 3rd rate.  
Rubber, jack pine and black oak.  
Thence from the cor. of secs. 34 and 35, on the S. bdy. of the township, which is an iron post, 2 ins. diam., projecting 9 ins. above ground, firmly set, with brass cap, marked and witnessed as described in the official record.  
N. 0° 33' W., on a true line bet. secs. 34 and 35 (S. & S. Over Level land, through scattering timber and under-wood growth, to a true line bet. secs. 34 and 35.  
The true point for the 1/4 sec. cor. of secs. 34 and 35, as determined from local bearing trees marked about 1909 by engineers of the Consumers Power Company, who report finding an original bearing tree.  
At the true point  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 34 and 35, with brass cap and witness tablet.  
1/4  
S 34° 15' E. 35.70  
From which  
The remains of an original bearing tree  
A stump hole and burned pine roots, bear N. 73° W., 65 lbs. distant.  
A fallen norway pine, 18 ins. diam., bears S. 46° E., 10 lbs. dist., with old blaze.  
A black oak, 12 ins. diam., bears N. 66° W., 62 lbs. dist., nhd. 1/4 S N B S.  
And now bearing trees, nhd. and S. side road A  
A norway pine, 22 ins. diam., bears S. 52° 30' E., 404 lbs. dist., nhd. 1/4 S 35° B S.  
1927

A jack pine, 7 ins. diam., bears S. 36° 30' E., 314 lbs. dist., nhd. 1/4 S 34° B S.  
211 lbs. dist., nhd. 1/4 S 34° B S.  
N. 0° 47' W., on a true line bet. secs. 34 and 35 (N. & S.)  
0.80 Road, bears NE. and SW.  
Proportional distance, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 25, 27, 34 and 35, with brass tablet nhd.  
From which  
A black oak, 3 ins. diam., bears N. 18° E., 130 lbs. dist., nhd. S & only.  
A jack pine, 6 ins. diam., bears S. 65° E., 294 lbs. dist., nhd. R. 24 W. R. 6 E. S. 35° B. 301 lbs.  
A jack pine, 10 ins. diam., bears S. 71° W., 303 lbs. dist., nhd. S 24° W. S 34° B S.  
A black oak, 2 ins. diam., bears N. 72° 30' W., 44 lbs. dist., nhd. S & only.  
Land, Level.  
Soil, sandy, 3rd rate.  
Rubber, jack pine and black oak.  
Undergrowth, young timber.  
H. 89° 07' E., on a true line bet. secs. 35 and 35 (N. & S.)  
2.00 Forest Service telephone line, bears NW. and SE.  
The true point for the 1/4 sec. cor. of secs. 26 and 35, which is marked by a wooden post, 4 x 4 x 24 ins., set about 1909 by engineers of the Consumers Power Company, who report finding both original bearing trees.  
In place of the wooden post, set and witness tablet  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 26 and 35 with brass cap and witness tablet.  
26 and 35 with brass cap and witness tablet.  
to the old boundary line on the S. side road A  
1927



14  
 Dependent Survey of the Subdivisional Lines.  
 T. 24 N., R. 6 E.

04.10	A local bearing tree	
	A Jack pine, 9 ins. diam., bears S. 72° 30' E., 214 lbs. dist., mtd. N B E. And new bearing trees	
04.11	A black oak, 4 ins. diam., bears N. 30° E., 216 lbs. dist., mtd. 1/4 S 26 B E.	
04.12	A Jack pine, 6 ins. diam., bears S. 35° W., 376 lbs. dist., mtd. 1/4 S 35 B E.	
04.13	Thence	
04.14	N. 88° 19' E., on a true line bet. secs. 26 and 35 (E-4)	
04.15	Road, bears N. and S. 72° 30' E.	
04.16	Road, bears N. and S. 72° 30' E.	
04.17	Road, bears N. and S. 72° 30' E.	
04.18	Road, bears N. 80° W. and S. 80° E.	
04.19	Ins. cor. of secs. 25, 26, 35 and 36.	
04.20	Land, level.	
04.21	Soil, sandy, 3rd rate.	
04.22	Timber, Jack pine and black oak.	
04.23	From the cor. of secs. 26, 27, 34 and 35.	
04.24	N. 0° 04' E., on a true line bet. secs. 26 and 27.	
04.25	Over level land, through scattering timber and light undergrowth.	
04.26	Forest Service telephone line, bears N. and S. Proportional distance.	
04.27	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 26 and 27, with brass cap mtd. 1/4 S 27 B E.	
04.28	From which	
04.29	A Jack pine, 5 ins. diam., bears N. 68° E., 130 lbs. dist., mtd. 1/4 S 26 B E.	
04.30	A Jack pine, 5 ins. diam., bears N. 65° 30' W., 130 lbs. dist., mtd. 1/4 S 27 B E.	
04.31	At a local corner, a wooden post, 4 x 4 x 24 ins. above ground, bears N. 37° 45' E., 39 lbs. distant. This corner was established by engineers of the Consumers Power Company, who also reestablished the cor. of secs. 22, 23, 26 and 27. The latter corner was found	

15  
 Dependent Survey of the Subdivisional Lines.  
 T. 24 N., R. 6 E.

04.32	unacceptable, as given below; consequently the local 1/4 sec. cor. of secs. 26 and 27 was not accepted.	
04.33	Road, bears N. and S. E.	
04.34	Road, bears E. and W.	
04.35	Begin descent of 75 feet over N. slope.	
04.36	Proportional distance.	
04.37	Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 22, 23, 26 and 27, with brass tablet mtd. 24 N B 6 E.	
04.38	From which	
04.39	A black oak, 6 ins. diam., bears N. 10° 15' E., 80 lbs. dist., mtd. 24 N B 6 E S 23 B E.	
04.40	A white oak, 8 ins. diam., bears N. 72° 15' W., 147 lbs. dist., mtd. 24 N B 6 E S 22 B E.	
04.41	No bearing trees available in secs. 26 and 27.	
04.42	A local corner, an iron pipe, 1 in. diam., 10 ins. above ground, bears S. 52° 45' W., 47 lbs. dist.	
04.43	This corner was established by engineers of the Consumers Power Company, about 1909, by single proportional measurement between the 1/4 sec. cor. of secs. 34 and 35 and the cor. of secs. 14, 15, 22 and 23. I reestablish the corner by double proportional measurement, adopting new measurement.	
04.44	Land, level and rolling.	
04.45	Soil, sandy, 3rd rate.	
04.46	Timber, Jack pine and black oak.	
04.47	Undergrowth, scrub oak.	
04.48	N. 86° 26' E., on a true line bet. secs. 23 and 26.	
04.49	Over gently rolling land, through very scattering timber and light undergrowth.	
04.50	Road, bears N. and S. W.	
04.51	Road, bears N. and S. W.	
04.52	Road, bears N. and S. W.	
04.53	Road, bears N. and S. W.	
04.54	Road, bears N. and S. W.	
04.55	Road, bears N. and S. W.	
04.56	Road, bears N. and S. W.	
04.57	Road, bears N. and S. W.	
04.58	Road, bears N. and S. W.	
04.59	Road, bears N. and S. W.	
04.60	Road, bears N. and S. W.	



Dependent Recovery of the Subdivisional Lines.  
E. 24 N. R. 6 E.

32.80	A short street, bears N. 52° 45' W. and S. 52° 45' E. through property of the Consumers Power Company, with eotages on the north side of street at 0.35, 2.55, 5.07, 7.25 and 9.03 chs. distant, respectively.
37.00	Five Channels Dam and Power House of the Consumers Power Company, on the An Sable River, bears North, 10 chs. distant. Road, bears NE. and SW. Proportional distance.
39.76	Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 25 and 26, with brass tablet mtd.
	1/4 S 23
	1/4 S 26
41.40	No bearing trees available in sec. 25.
42.50	Right bank of the An Sable River, course SE.
47.85	Electric power transmission line, bears NW. and SE. left bank of the An Sable River.
71.60	Enter dense poplar timber.
79.55	Leave rolling land, enter tamarack and cedar swamp, bears NE. and SW.
	From the cor. of secs. 23, 24, 25 and 26.
	N. 0° 14' W., on a true line bet. secs. 22 and 25.
	Over gently rolling land, through very scattering timber and light undergrowth.
1.80	Road, bears E. and W.
8.50	Electric power transmission line, bears N. 72° 30' W. and S. 72° 30' E.
13.80	South shore of Five Channels Basin on the An Sable

Dependent Recovery of the Subdivisional Lines.  
E. 24 N. R. 6 E.

11.60	River, bears N. 60° E. and S. 60° W. North shore of Basin, bears NE. and SW. Thence over swampy land, through dense young poplar and alder.
40.38	Proportional distance.
	Set an iron post, 5 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 22 and 25, with brass cap mtd.
	1/4
	1/4 S 22
	1/4 S 25
	From which
	A poplar, 8 ins. diam., bears N. 69° 30' E., 49 lbs. dist., mtd. 1/4 S 23 B
	A poplar, 6 ins. diam., bears N. 66° W., 26 lbs. dist., mtd. 1/4 S 22 B
49.20	Road, bears E. and W.
52.20	Leave swamp, bears NW. and SE. Ascend 75 feet over SW. slope; enter jack pine and black oak timber.
55.40	Top of ascent, bears NW. and SE. Thence over level land.
60.77	The true point for the cor. of secs. 14, 15, 22 and 23, which is marked by an iron pipe, 1 in. diam., 10 ins. above ground, the corner was reestablished about 1909 by engineers of the Consumers Power Company, who reported finding the original post and one bearing tree.
	In place of the iron pipe.
	Set an iron post, 5 ft. long, 2 ins. diam., 27 ins. in the ground, for reestablished cor. of secs. 14, 15, 22 and 25, with brass cap mtd.
	1/4 N 6 E
	1/4 S 14
	From which
	A logical bearing tree
	A white oak, 10 ins. diam., bears S. 63° W., 120 lbs. dist., mtd. N B
	And new bearing trees
	A white oak, 9 ins. diam., bears N. 7° 30' E., 41 lbs. dist., mtd. S 24 N R 6 E S 14 B E.



Dependent Recovery of the Subdivisional Lines.  
R. 24 N., R. 6 E.

Chains

A white oak, 6 ins. diam., bears S. 37° E., 44 lbs. dist., nhd. r 24 N R 6 E S 23 B R.

A white oak, 8 ins. diam., bears S. 66° 15' W., 132 lbs. dist., nhd. r 24 N R 6 E S 22 B R.

A white pine, 16 ins. diam., bears N. 43° W., 201 lbs. dist., nhd. r 24 N R 6 E S 15 B R.

Land, level and gently rolling.

Soil, sandy, 3rd rate.

Timber, poplar, jack pine, black oak.

Undergrowth, young timber and alder.

N. 89° 02' E., on a true line bet. secs. 14 and 25.

Over gently rolling land, through timber and undergrowth, bears N. and S. r 24 N R 6 E S 23 B R.

Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 14 and 25, with brass cap nhd. r 24 N R 6 E S 23 B R.

From which

A Norway pine, 8 ins. diam., bears N. 45° E., 92 lbs. dist., nhd. 1/4 S 14 B R.

A jack pine, 8 ins. diam., bears S. 62° W., 200 lbs. dist., nhd. 1/4 S 23 B R.

From the cor. of secs. 13, 14, 23 and 24.

Land, gently rolling.

Soil, sandy, 3rd rate.

Timber, oak, jack pine, poplar.

Undergrowth, young timber.

From the cor. of secs. 14, 15, 22 and 23.

N. 0° 04' W., on a true line bet. secs. 14 and 15.

Over level land, through timber and undergrowth.

After scattering timber, bears N. and W.

Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 14 and 15.

Dependent Recovery of the Subdivisional Lines.  
R. 24 N., R. 6 E.

14 and 15, with brass cap nhd.

1/4

S 15 S 14

1927

From which

A local bearing tree

A white oak, 26 ins. diam., bears N. 28° 30' W., 28 lbs. dist., nhd. N B R (No local cor. was found).

And now bearing trees

A jack pine, 11 ins. diam., bears N. 73° 30' E., 75 lbs. dist., nhd. 1/4 S 14 B R.

A jack pine, 11 ins. diam., bears S. 45° 30' W., 79 lbs. dist., nhd. 1/4 S 15 B R.

94.10 Road, bears W. and S.

Proportional distance.

Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 10, 11, 14 and 15, with brass tablet nhd.

r 24 N R 6 E S 15 S 14

1927

From which

A Norway pine, 14 ins. diam., bears N. 79° E., 338 lbs. dist., nhd. r 24 N R 6 E S 11 B R.

A jack pine, 7 ins. diam., bears S. 76° 30' E., 23 lbs. dist., nhd. r 24 N R 6 E S 14 B R.

A Norway pine, 15 ins. diam., bears S. 12° 30' W., 308 lbs. dist., nhd. r 24 N R 6 E S 15 B R.

A black oak, 6 ins. diam., bears N. 82° W., 43 lbs. dist., nhd. r 24 N R 6 E S 10 B R.

Land, level.

Soil, sandy, 3rd rate.

Timber, jack pine and black oak.

Undergrowth, young timber.

N. 89° 03' E., on a true line bet. secs. 11 and 14.

Over level land, through timber and light undergrowth.

Road, bears N. and S.

Proportional distance.



Dependent Reserve of the Subdivisional Lines,  
R. 24 N., R. 6 E.

Chains  
Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 11 and 14, with brass tablet nhd.

S 11  
1/4 S 11

From which  
1927

Jack pine, 6 ins. diam., bears N. 25° 30' W., 95 lbs. dist., nhd. 1/4 S 11 B F.

Jack pine, 6 ins. diam., bears S. 31° 15' E., 92 lbs. dist., nhd. 1/4 S 11 B F.

80.30 The cor. of secs. 11, 12, 13 and 14.  
Land, level.

Soil, sandy, 3rd rate.  
Timber, jack pine and black oak.

Undergrowth, young timber.

From the cor. of secs. 10, 11, 14 and 15.

N. 0° 31' E., on a true line bet. secs. 10 and 11.  
Over level land, through scattering timber and light undergrowth.

31.00 Head, bears NW. and SE.

40.06 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 10 and 11, with brass cap nhd.

1/4  
S 10 S 11

From which  
1927

A black oak, 6 ins. diam., bears N. 87° 30' E., level, nhd.

A black oak, 6 ins. diam., bears S. 59° 15' W., 117 lbs. dist., nhd. 1/4 S 10 B F.

80-12 Proportional distance.

Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 2, 3, 10 and 11, with brass tablet nhd.

Dependent Reserve of the Subdivisional Lines,  
R. 24 N., R. 6 E.

Chains  
Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 10 and 11, with brass tablet nhd.

S 11  
1/4 S 11

From which  
1927

A black oak, 11 ins. diam., bears E. 75° E., 141 lbs. dist., nhd. 24 N R 6 E S 2 B F.

A black oak, 6 ins. diam., bears S. 82° 30' E., 205 lbs. dist., nhd. 24 N R 6 E S 11 B F.

A jack pine, 9 ins. diam., bears S. 15° W., 240 lbs. dist., nhd. 24 N R 6 E S 10 B F.

A black oak, 10 ins. diam., bears N. 73° W., 34 lbs. dist., nhd. 24 N R 6 E S 3 B F.

A local corner, a wooden post, 3 x 3 x 24 ins. above ground, bears S. 80° W., 42 lbs. dist. This corner measurement, and was not accepted for that reason.

Land, level.  
Soil, sandy, 3rd rate.  
Timber, jack pine and black oak.

Undergrowth, young oak.

N. 88° 59' E., on a true line bet. secs. 2 and 11.  
Over level land, through scattering timber.

10.50 Enter grassy marsh, bears N. and S.

20.20 Leave marsh, bears N. and S. Enter scattering timber.

40.05 Proportional distance.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 2 and 11, with brass cap nhd.

1/4  
S 11

From which  
1927

A Norway pine, 20 ins. diam., bears N. 45° E., level, nhd.

108 lbs. dist., nhd. N B F.

A jack pine, 9 ins. diam., bears S. 68° E., 151 lbs. dist., nhd. 1/4 S 11 B F.

A local corner, a wooden post, 4 x 4 x 24 ins. above ground, bears S. 80° W., 42 lbs. dist. This corner measurement, and was not accepted for that reason.



Dependent Recovery of the Subdivisional Lines.  
E. 24 N., R. 6 E.

Chains

Ground, bears S. 36° 30' E., 34 lbs. dist. No original evidence in support of this local corner could be found.

75.50 Road, bears N. and S.

80.10 The cor. of secs. 1, 2, 11 and 12. See Road A Land, level.

205 Soil, sandy, 3rd rate. Timber, jack pine and black oak.

From the cor. of secs. 2, 3, 10 and 11. N. 0° 01' E., on a true line bet. secs. 2 and 3.

Over level land, through scattering timber and undergrowth.

48.06 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 2 and 3, with brass cap and.

1/4  
S 3 | S 2  
1927

From which  
A jack pine, 8 ins. diam., bears N. 76° W., 114 lbs. dist., and 1/4 S 3 B T.

A black oak, 6 ins. diam., bears S. 63° 30' E., 48 lbs. dist., and 1/4 S 2 B T.

the cor. of secs. 2, 3, 34 and 35, on the N. by. of the township, previously described.

Land, level. Soil, sandy, 3rd rate. Timber, black oak and jack pine. Undergrowth, young timber.

From the cor. of secs. 3, 4, 33 and 34, on the S. by. of the township, which is an iron post, 2 ins. diam., projecting 9 ins. above ground, with brass cap, and witnessed as described in the official record.

N. 0° 40' W., on a true line bet. secs. 33 and 34.

Over level land, through scattering timber and light undergrowth.

9.70 Road, bears N. 70° E. and S. 70° W.

Dependent Recovery of the Subdivisional Lines.  
E. 24 N., R. 6 E.

Chains

Proportional distance.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 33 and 34, with brass cap and.

80.55 Proportional distance.

Set an iron post, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 27, 28, 33 and 34, with brass tablet and.

24 N. R. 6 E  
S 28 | S 27  
S 33 | S 34  
1927

From which  
A jack pine, 5 ins. diam., bears S. 68° 30' E., 26 lbs. dist., and 1/4 S 34 B T.

A jack pine, 10 ins. diam., bears S. 62° 15' W., 131 lbs. dist., and 1/4 S 33 B T.

From which  
A black oak, 9 ins. diam., bears N. 30° E., 248 lbs. dist., and 1/4 N 6 E S 27 B T.

A black oak, 5 ins. diam., bears S. 50° E., 66 lbs. dist., and 1/4 N 6 E S 34 B T.

A jack pine, 7 ins. diam., bears S. 30° 30' W., 123 lbs. dist., and 1/4 N 6 S 33 B T.

A black oak, 9 ins. diam., bears N. 33° W., 79 lbs. dist., and 1/4 N 6 S 28 B T.

Land, level. Soil, sandy, 3rd rate. Timber, black oak and jack pine. Undergrowth, young timber.

N. 88° 58' E., on a true line bet. secs. 27 and 34. Over level land, through scattering timber and undergrowth.

Proportional distance.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in



24  
Dependent Recovery of the Substantial Lines,  
R. 24 N., R. 6 E.

Chains the ground, for reestablished 1/4 sec. cor. of secs. 27 and 34, with brass cap nhd.

From which  
S 27  
S 34  
1927

A black oak, 6 ins. diam., bears E. 66° W.,  
66 lbs. dist., nhd. 1/4 S 27 B P.

A black oak, 9 ins. diam., bears S. 58° E.,  
865 lbs. dist., nhd. 1/4 S 34 B P.

The cor. of secs. 26, 27, 34 and 35.  
Land, level.  
Soil, sandy, 3rd rate.  
Timber, black oak and jack pine.  
Undergrowth, young timber.

From the cor. of secs. 27, 28, 33 and 34.  
N. 0° 13' E., on a true line bet. secs. 27 and 28.  
Over level land, through very scattering timber and light undergrowth.

20.60 Road, bears N. 55° E. and S. 55° W.

32.00 Enter medium timber, bears E. and W.

40.12 Proportional distance.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 27 and 28, with brass cap nhd.

1/4  
S 26 | S 27  
1927

From which  
A black oak, 1 1/2 ins. diam., bears S. 77° 30' E.,  
49 lbs. dist., nhd. 1/4 S 27 B P.

A jack pine, 8 ins. diam., bears S. 55° 30' W.,  
37 lbs. dist., nhd. 1/4 S 28 B P.

65.00 Enter very scattering timber, bears E. and W.

60.25 Proportional distance.  
Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 21, 22, 27 and 28, with brass tablet nhd.

25  
Dependent Recovery of the Substantial Lines,  
R. 24 N., R. 6 E.

From which  
S 21 | S 22  
S 28 | S 27  
1927

A black oak, 6 ins. diam., bears N. 61° 30' E.,  
220 lbs. dist., nhd. R 24 N R 6 S 22 B P.

A jack pine, 10 ins. diam., bears S. 27° E., 399  
lbs. dist., nhd. R 24 N R 6 S 27 B P.

A black oak, 10 ins. diam., bears S. 55° W., 65  
lbs. dist., nhd. R 24 N R 6 S 28 B P.

A jack pine, 10 ins. diam., bears N. 37° 30' E.,  
349 lbs. dist., nhd. R 24 N R 6 B 21 B P.

A local corner, re-established from post, 1 in. diam.,  
10 ins. above ground, bears E. 45° S., 65 lbs.  
dist. The post is marked on cap,  
21 | 22  
28 | 27

work was set by the U. S. Forest Service in place of  
a wooden post, which had been set on single prop-  
tion measurement by engineers of the Commercial  
Power Company, about 1909.

Land, level.  
Soil, sandy, 3rd rate.  
Timber, jack pine and black oak.  
Undergrowth, scrub oak.

E. 88° 55' E., on a true line bet. secs. 22 and 27.  
Over level land, through scattering timber and light  
undergrowth.

2.60 Forest Service telephone line, bears N. and SE.  
Proportional distance.

79.44 Set an iron post, 3 ft. long, 1 in. diam., 38 ins. in  
the ground, for reestablished 1/4 sec. cor.  
of secs. 22 and 27, with brass cap nhd.

From which  
S 22  
S 27  
1927

A jack pine, 10 ins. diam., bears E. 26° E., 120  
lbs. dist., nhd. 1/4 S 22 B P.







Dependent Recovery of the Subdivisional Lines,  
P. 24 N., R. 6 E.

55.40 From the cor. of secs. 15, 16, 21 and 22, N. 0° 42' W. on a true line, bet. secs. 15 and 16. Over level land, through cedar and tamarack swamp. Road, bears N. 58° W. and S. 58° E.

4.15 Leave swamp, bears N. 70° W. and S. 60° E. Ascend 50 feet over SW slope; enter scattering pine and oak timber.

39.00 Top of ascent; thence over gently rolling land. Proportional distance.

35.00 Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 15 and 16, with brass tablet nhd.

80.25 From the cor. of secs. 9, 10, 15 and 16, S 16° 15' E. 228.88 N. 1927. Set level 1910

From which  
A jack pine, 10 ins. diam., bears N. 72° E. 30.0  
37 lbs. dist., nhd. 1/4 S 15 B T.  
A jack pine, 10 ins. diam., bears N. 42° 45' W., 68 lbs. dist., nhd. 1/4 S 16 B T.

Dependent Recovery of the Subdivisional Lines,  
P. 24 N., R. 6 E.

which is marked by a wooden post, 3 x 3 x 24 ins. above ground, set about 1909 by engineers of the Consumers Power Company, who report finding the original corner post lying on the ground and both bearing trees. In place of the wooden post, Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 9, 10, 15 and 16, with brass tablet nhd.

7 24 N. R. 6 E  
S 9 S 10  
S 16 S 15  
1921

The remains of the original bearing trees  
A fallen Norway pine, 24 ins. diam., bears N. 50° E., 110 lbs. dist., with all marks burned and weathered off.

A stump hole and pine roots, bears N. 61° 30' W., 71 lbs. dist.

And a local bearing tree, bears N. 60° 30' W., 63 lbs. dist., nhd. 6 ins. diam., bears N. 63° E., 64 lbs. dist., nhd. N. B. T.

And new bearing trees  
A jack pine, 10 ins. diam., bears N. 19° E., 187 lbs. dist., nhd. 24 N R 6 E S 10 B T.  
A black oak, 8 ins. diam., bears S. 43° 30' E., 169 lbs. dist., nhd. 24 N R 6 E S 15 B T.  
A black oak, 6 ins. diam., bears S. 52° W., 94 lbs. dist., nhd. 24 N R 6 E S 16 B T.  
A jack pine, 8 ins. diam., bears N. 69° 45' W., 140 lbs. dist., nhd. 24 N R 6 E S 9 B T.

Land, level and rolling.  
Soil, sandy, 3rd rate, in swamp; sandy, 3rd rate, on upland.  
Timber, cedar, tamarack, jack pine, black oak.  
Undergrowth, young timber and alder.

N. 88° 21' E., on a true line bet. secs. 10 and 15. Over level land, through scattering timber.



340	Dim road, bears N. and S.
40.15	Proportional distance.
62.70	Head, bears S. 70° E. and N. 70° W.
80.75	Proportional distance.
62.40	Head, bears N. and S.
80.75	The cor. of seos. 10, 11, 14 and 15.
40.15	Proportional distance.
62.40	Head, bears N. and S.
80.75	The cor. of seos. 10, 11, 14 and 15.
40.15	Proportional distance.
62.40	Head, bears N. and S.
80.75	The cor. of seos. 10, 11, 14 and 15.

31.50	Head, bears N. and S.
40.02	Proportional distance.
31.50	Head, bears N. and S.
40.02	Proportional distance.
31.50	Head, bears N. and S.
40.02	Proportional distance.
31.50	Head, bears N. and S.
40.02	Proportional distance.



Dependent Recovery of the Subdivisional Lines,  
T. 24 N., R. 6 E.

34.80	Chains Light undergrowth. Fence, bears E. and W.
37.50	Fence, bears N. 2° W. and S. 2° E. Proportional distance.
40.17	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of sec. 3 and 4, with brass cap and 1/4 5 4   S 3 From which A white oak, 10 ins. diam., bears N. 84° 45' E., 50 lbs. dist., and 1/4 S 3 B E. A white oak, 12 ins. diam., bears N. 56° E., 39 lbs. dist., and 1/4 S 4 B E. Corner of field, edges bears N. and E. Field begins to W. of line, edge bears W. Leave fields to E. and W. of line.
69.00	Enter timber, bears E. and W.
76.31	Fence, bears E. and W. Enter road.
76.94	In the corner of sec. 3 and 4, on the N. side of the township, previously described. Land, gently rolling. Soil, south & white, sandy, 3rd rate; north & white, clay loam, 2nd rate. Timber, oak and jack pine. Undergrowth, young timber.
82.00	From the cor. of secs. 4, 5, 32 and 33, on the S. side of the township, which is an iron post, 2 ins. diam., projecting 9 ins. above ground, with brass cap, and witnessed as described in the official record. N. 0° 38' W., on a true line bet. secs. 32 and 33. Over level land, through scattering timber and light undergrowth.
83.00	Enter recent burn and dead timber, bears E. and W.
23.00	Enter very scattering timber, bears E. and W.
39.97	Proportional distance.

Dependent Recovery of the Subdivisional Lines,  
T. 24 N., R. 6 E.

45.80	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 32 and 33, with brass cap and 1/4 5 3   S 3 From which A jack pine, 8 ins. diam., bears S. 45° E., 184 lbs. dist., and 1/4 S 3 B E. A jack pine, 11 ins. diam., bears N. 29° W., 50 lbs. dist., and 1/4 S 32 B E. Road, bears N. 55° E. and S. 55° W.
79.94	Road, bears N. 55° E. and S. 55° W. Proportional distance. Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 28, 29, 32 and 33, with brass tablet and E 24 N R 6 E S 29 S 28 S 32 S 33 From which A jack pine, 6 ins. diam., bears N. 82° 30' E., 147 lbs. dist., and E 24 N R 6 E S 28 B E. A Norway pine, 14 ins. diam., bears S. 40° 30' E., 219 lbs. dist., and E 24 N R 6 E S 33 B E. A black oak, 11 ins. diam., bears S. 60° W., 31 lbs. dist., and E 24 N R 6 E S 32 B E. A jack pine, 7 ins. diam., bears E. 29° 30' W., 135 lbs. dist., and E 24 N R 6 E S 29 B E. Land, level. Soil, sandy, 3rd rate. Timber, jack pine and black oak. Undergrowth, scrub oak.
83.00	Road, bears N. and S.
31.89	Over level land, through scattering timber. Road, bears N. and S. Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs.



Dependent Recovery of the Subdivision Lines,  
E. 24 N., R. 6 E.

79-76	From the cor. of secs. 27, 28, 33 and 34. The cor. of secs. 27, 28, 33 and 34. Land, level, sandy, 3rd rate. Soil, sandy, 3rd rate. Timber, black oak, jack pine.	28° and 33, with brass cap. nhd. 1/4 S 28 B E. 149 lbs. dist., nhd. 1/4 S 28 B E. A Norway pine, 11 ins. diam., bears S. 39° 30' W., 54 lbs. dist., nhd. 1/4 S 33 B E. The cor. of secs. 27, 28, 33 and 34. Land, level, sandy, 3rd rate. Soil, sandy, 3rd rate. Timber, black oak, jack pine.
79-78	From the cor. of secs. 28, 29, 32 and 33. H. 0° 15' E., on a true line bet. secs. 28 and 29. Over level land, through very scattering timber and light undergrowth.	28° and 33, with brass cap. nhd. 1/4 S 28 B E. 149 lbs. dist., nhd. 1/4 S 28 B E. A Norway pine, 11 ins. diam., bears S. 39° 30' W., 54 lbs. dist., nhd. 1/4 S 33 B E. The cor. of secs. 27, 28, 33 and 34. Land, level, sandy, 3rd rate. Soil, sandy, 3rd rate. Timber, black oak, jack pine.
79-97	Road, bears N. and SW. Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 28 and 29, with brass cap nhd.	28° and 33, with brass cap. nhd. 1/4 S 28 B E. 149 lbs. dist., nhd. 1/4 S 28 B E. A Norway pine, 11 ins. diam., bears S. 39° 30' W., 54 lbs. dist., nhd. 1/4 S 33 B E. The cor. of secs. 27, 28, 33 and 34. Land, level, sandy, 3rd rate. Soil, sandy, 3rd rate. Timber, black oak, jack pine.
79-94	Proportional distance. Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 20, 21, 28 and 29, with brass tablet nhd.	28° and 33, with brass cap. nhd. 1/4 S 28 B E. 149 lbs. dist., nhd. 1/4 S 28 B E. A Norway pine, 11 ins. diam., bears S. 39° 30' W., 54 lbs. dist., nhd. 1/4 S 33 B E. The cor. of secs. 27, 28, 33 and 34. Land, level, sandy, 3rd rate. Soil, sandy, 3rd rate. Timber, black oak, jack pine.

Dependent Recovery of the Subdivision Lines,  
E. 24 N., R. 6 E.

79-95	From which. A Norway pine, 16 ins. diam., bears N. 26° 30' W., 117 lbs. dist., nhd. 1/4 S 21 B E. A jack pine, 10 ins. diam., bears S. 12° W., 117 lbs. dist., nhd. 1/4 S 28 B E. Land, level. Soil, sandy, 3rd rate. Timber, jack pine and black oak. Undergrowth, young timber.	89 lbs. dist., nhd. E 24 N R 6 E S 28 B E. A jack pine, 10 ins. diam., bears S. 63° 15' W., 210 lbs. dist., nhd. E 24 N R 6 E S 29 B E. A jack pine, 10 ins. diam., bears N. 26° W., 209 lbs. dist., nhd. E 24 N R 6 E S 28 B E. A local corner, which is a galvanised-iron post, 1 1/2 ins. diam., 10 ins. above ground, bears N. 5° 15' E., 95 lbs. dist. This post was set by the U.S. Forest Service in place of a wooden post, set about 1909 by engineers of the Consumers Power Company, by single proportional measurement on the latitudinal line.
79-96	From which. A Norway pine, 16 ins. diam., bears N. 26° 30' W., 117 lbs. dist., nhd. 1/4 S 21 B E. A jack pine, 10 ins. diam., bears S. 12° W., 117 lbs. dist., nhd. 1/4 S 28 B E. Land, level. Soil, sandy, 3rd rate. Timber, jack pine and black oak. Undergrowth, young timber.	89 lbs. dist., nhd. E 24 N R 6 E S 28 B E. A jack pine, 10 ins. diam., bears S. 63° 15' W., 210 lbs. dist., nhd. E 24 N R 6 E S 29 B E. A jack pine, 10 ins. diam., bears N. 26° W., 209 lbs. dist., nhd. E 24 N R 6 E S 28 B E. A local corner, which is a galvanised-iron post, 1 1/2 ins. diam., 10 ins. above ground, bears N. 5° 15' E., 95 lbs. dist. This post was set by the U.S. Forest Service in place of a wooden post, set about 1909 by engineers of the Consumers Power Company, by single proportional measurement on the latitudinal line.
79-97	Road, bears N. and SW. Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 21 and 28, with brass cap nhd.	89 lbs. dist., nhd. E 24 N R 6 E S 28 B E. A jack pine, 10 ins. diam., bears S. 63° 15' W., 210 lbs. dist., nhd. E 24 N R 6 E S 29 B E. A jack pine, 10 ins. diam., bears N. 26° W., 209 lbs. dist., nhd. E 24 N R 6 E S 28 B E. A local corner, which is a galvanised-iron post, 1 1/2 ins. diam., 10 ins. above ground, bears N. 5° 15' E., 95 lbs. dist. This post was set by the U.S. Forest Service in place of a wooden post, set about 1909 by engineers of the Consumers Power Company, by single proportional measurement on the latitudinal line.



Dependent Recovery of the Subdivisional Lines,  
R. 24 N., R. 6 E.

Dependent Recovery of the Subdivisional Lines,  
R. 24 N., R. 6 E.

Chains From the cor. of secs. 20, 21, 28 and 29.

H. 0° 13' E., on a true line bet. secs. 20 and 21.  
Over level land, through scattering timber and light  
undergrowth.

1.04 Forest Service telephone line, bears N. 89° E. and  
S. 89° W.

1.15 Road, bears N. 89° E. and S. 89° W.

34.62 Electric power transmission line, bears N. 46° 45' E.  
and S. 46° 45' W.

36.00 Begin descent of 80 feet over H. slope.

39.97 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for reestablished 1/4 sec. cor. of secs.  
20 and 21, with brass cap mtd.

1/4

S 20 S 21

1927

From which

A norway pine, 5 ins. diam., bears N. 52° E.,  
37 lbs. dist. mtd. 1/4 S 21 N E.

A norway pine, 6 ins. diam., bears S. 31° 45' W.,  
105 lbs. dist. mtd. 1/4 S 20 N E.

42.00 Foot of descent, bears NE. and SW. Enter cedar swamp.

51.10 S. shore of Loud Basin on the Au Sable River, bears  
N. 70° E. and S. 70° W.

Change over waters of Basin.

74.10 H. shore of Loud Basin, bears NE. and SW.

Enter timber; thence over level land.

79.94 The true point for the cor. of secs. 16, 17, 20 and 21,  
which is marked by an iron pipe, 1 in. diam., 8 ins.  
above ground, set about 1907 by engineers of the  
Vermont Power Company from an original bearing tree  
in place of the iron pipe.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
the ground, for reestablished cor. of secs. 16, 17,  
20 and 21, with brass cap mtd.

From the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for reestablished 1/4 sec. cor. of secs.  
16 and 21, with brass cap mtd.

From which

A fallen norway pine, 12 ins. diam., bears S. 37° 15'  
E., 177 lbs. dist. mtd. N E 24 N E.

A black oak, 6 ins. diam., bears N. 59° 30' W.,  
166 lbs. dist. mtd. N E 24 N E.

A jack pine, 2 ins. diam., bears N. 68° 15' E.,  
106 lbs. dist. mtd. N E 24 N E.

A norway pine, 8 ins. diam., bears S. 8° E., 126 lbs.  
dist. mtd. E 24 N E S 21 N E.

A poplar, 5 ins. diam., bears S. 28° 30' W., 39 lbs.  
dist. mtd. E 24 N E S 21 N E.

A poplar, 4 ins. diam., bears N. 18° 45' W., 33 lbs.  
dist. mtd. E 24 N E S 17 N E.

Land, level and hilly.

Soil, sandy, 3rd rate.

Timber, jack pine, black oak, cedar, poplar, tamarack,  
undergrowth, young timber.

H. 88° 04' E., on a true line bet. secs. 16 and 21.

Over level land, through young timber and undergrowth.

Power House at Loud Dam on the Au Sable River, bears  
South, 20 chains distant.

44.90 Electric power transmission line, bears N. 26° W. and  
S. 26° E.

Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for reestablished 1/4 sec. cor. of secs.  
16 and 21, with brass cap mtd.

From which

A white pine, 7 ins. diam., bears N. 70° 45' W.,  
119 lbs. dist. mtd. 1/4 S 16 N E.

A norway pine, 11 ins. diam., bears S. 55° 45' W.,



Dependent Resurvey of the Subdivision Lines,  
P. 24 T. R. 6 E.

Chains	63 lns. dist., mid. 1/4 S 21 B E.
42.70	The N. shore of flowage of the Five Channels-Basin on Middle Sabie River; bears N. 60° E.; and S. 60° W. Thence across waters of Basin.
70.20	The N. shore of flowage of Five Channels-Basin; bears N. and S. Thence over level land, through timber.
79.34	The cor. of secs. 15; 16, 21 and 22. 1/4 sec. Land, level. Soil, sandy, 3rd rate. Timber, poplar, jack pine and a few Norway and white pines. Undergrowth, young timber, alder and service.
25.66	From the cor. of secs. 15, 17, 20 and 21. N. 0° 45' W. on a true line bet. secs. 16 and 17. Over level land, through young timber and undergrowth.
23.80	Enter low, wet land, bears W. and SE.
25.66	Electric power transmission line, bears N. 47° W. and S. 47° E.
26.50	Leave wet land, bears W. and SE.
30.60	Thence over gently rolling land. Enter poplar and cedar swamp, bears E. and W.
40.24	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 16 and 17 with brass cap mid.
	From which
	A balsam of 11 ins. diam., bears N. 83° 15' E., 31 lns. dist., mid. 1/4 S 16 B E.
	To an oak, 5 ins. diam., bears S. 81° W., 17 lns. dist., mid. 1/4 S 17 B E.
80.48	Proportional distance.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for reestablished cor. of secs. 8, 9, 16 and 17, with brass cap mid.

Dependent Resurvey of the Subdivision Lines,  
P. 24 T. R. 6 E.

	24 B R 6 E
	8 8   8 9
	8 17   8 16
	1927
	From which
	A spruce, 10 ins. diam., bears N. 87° E., 10 lns. dist., mid. 24 N R 6 E S 9 B E.
	A balsam, 10 ins. diam., bears S. 47° 30' E., 44 lns. dist., mid. 24 N R 6 E S 16 B E.
	A balsam, 6 ins. diam., in sec. 17, bearing not recorded, 14 lns. dist., mid. 24 N R 6 E S 17 B E.
	An oak, 6 ins. diam., in sec. 8, bearing not recorded, 14 lns. dist., mid. 24 N R 6 E S 8 B E.
	Land, level.
	Soil, S. 3, sandy, 3rd rate; N. 3, muck, 3rd rate. Timber, poplar, cedar, balsam, spruce, tamarack. Undergrowth, young timber and alder.
	N. 88° 17' E., on a true line, bet. secs. 9 and 16. Over level land, through cedar and balsam swamp.
	Leave cedar swamp, bears W. and SE. Ascend, 50 feet over a 25% slope. Enter sprouting oak and pine timber and light undergrowth.
26.60	Top of ascent, bears W. and SE. Thence over level land.
39.69	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 9 and 16 with brass cap mid.
	From which
	A black oak, 5 ins. diam., bears N. 5° E., 55 lns. dist., mid. 1/4 S 9 B E.
	A white oak, 10 ins. diam., bears S. 14° E., 46 lns. dist., mid. 1/4 S 16 B E.
79.38	The cor. of secs. 9, 10, 15 and 16.
	Land, level.
	Soil, muck, 3rd rate, in swamp; sandy, 3rd rate, on upland.
	Timber, cedar, oak, balsam, jack pine, etc.



Dependent Recovery of the Subdivisional Lines,  
T. 24 N., R. 6 E.

Chains	Undergrowth, young timber and alder.
	From the cor. of secs. 8, 9, 16 and 17. N. 0° 21' E., on a true line bet. secs. 8 and 9. Over level land, through cedar swamp.
5.20	Leave swamp, bears E. and W. Ascend 30 feet over south slope. Enter oak timber.
6.50	Top of ascent. Thence over level land.
8.50	Enter cedar and balsam swamp, bears E. and W.
13.60	Leave cedar swamp, ascend 40 feet over south slope, edge bears N. 70° W. and S. 70° E.
15.70	Top of ascent. Thence over gently rolling land, through scattering timber and undergrowth.
26.00	The S. shore of a bay of a shallow, grassy lake, bears W. and E.
28.70	N. shore of bay of lake, bears W. and SE.
37.65	South shore of lake, bears N. 60° E. and S. 50° W. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness corner to the reestablished 1/4 sec. cor. of secs. 8 and 9, with brass cap nkt. W. C.
	1/4 S 8   S 9 1927
	From which A white pine, 10 ins. diam., bears S. 51° 45' E., 97 lbs. dist., nkt. W C 1/4 S 9 B E. A white pine, 10 ins. diam., bears S. 16° W., 65 lbs. dist., nkt. W C 1/4 S 8 B E. Thence over lake. Proportional distance.
40.24	The true point for the reestablished 1/4 sec. cor. of secs. 8 and 9, falls in lake.
51.70	N. shore of lake, bears N. 60° E. and S. 35° W. Thence over rolling land, through timber and light undergrowth.
67.80	S. shore of a shallow, grassy pond, bears E. and W.
72.60	N. shore of pond, bears W. and S. 60° E.
80.48	Proportional distance.

Dependent Recovery of the Subdivisional Lines,  
T. 24 N., R. 6 E.

Chains	Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 4, 5, 8 and 9, with brass tablet nkt.
	From which A jack pine, 6 ins. diam., bears N. 20° E., 75 lbs. dist., nkt. T 24 N R 6 E S 4 B E. A black oak, 6 ins. diam., bears S. 64° E., 41 lbs. dist., nkt. T 24 N R 6 E S 9 B E. A norway pine, 14 ins. diam., bears S. 6° W., 133 lbs. dist., nkt. T 24 N R 6 E S 8 B E. A jack pine, 5 ins. diam., bears N. 34° 30' W., 70 lbs. dist., nkt. T 24 N R 6 E S 5 B E. Land, level and rolling. Soil, sandy, 3rd rate. Timber, black oak, jack-pine, cedar, and a few norway pines. Undergrowth, young timber.
30.00	Road, bears N. 60° W. and S. 60° E.
39.71	The true point for the 1/4 sec. cor. of secs. 4 and 9, which is marked by a wooden post, 4 x 4 x 24 ins. above ground, witnessed by the remains of original bearing trees. In place of the wooden post, set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 4 and 9, with brass tablet nkt.
	From which The remains of the original bearing trees A stump hole and pine fragments, bear N. 64° E., 42 lbs. distant. A pine, 30 ins. diam., bears N. 30° W., 70 lbs.



Dependent Recovery of the Subdivisional Lines.  
P. 24 R. 1, R. 6 E.

Chains

dist., with all marks burnt and weathered off.  
And local bearing trees

A jack pine, 8 ins. diam., bears N. 53° 15' E.,  
32 lbs. dist., mtd. with blaze.

A jack pine, 8 ins. diam., bears S. 34° 30' E.,  
88 lbs. dist., mtd. 1/4.

And new bearing trees  
A Norway pine, 12 ins. diam., bears E. 4° 45' E.,  
155 lbs. dist., mtd. 1/4 S 4 B F.

A white oak, 10 ins. diam., bears S. 29° 30' W.,  
158 lbs. dist., mtd. 1/4 S 9 B F.

Thence  
E. 86° 03' E., on a true line bet. secs. 4 and 9 (R. 4).  
the cor. of secs. 3, 4, 9 and 10.

Land, level.  
Soil, sandy, 3rd rate.  
Timber, jack pine and black oak.

From the cor. of secs. 4, 5, 8 and 9.  
E. 0° 05' W., on a true line bet. secs. 4 and 5.  
Over gently rolling land, through scattering timber.

15.40

26.00

40.24

1927

From which

A white oak, 6 ins. diam., bears E. 66° E.,  
105 lbs. dist., mtd. 1/4 S 4 B F.

A white oak, 6 ins. diam., bears N. 9° 30' W.,  
48 lbs. dist., mtd. 1/4 S 5 B F.

Enter scattering timber, bears E. and W.  
Dm road, bears W. and SE.

72.00

78.56

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of  
the township, previously described.

Dependent Recovery of the Subdivisional Lines,  
P. 24 R. 1, R. 6 E.

Chains

Land, gently rolling.  
Soil, sandy, 3rd rate.  
Timber, jack pine, black oak and white oak.

From the cor. of secs. 31 and 32, on the S. bdy. of the  
township, which is an iron post, 2 ins. diam., pro-

jecting 9 ins. above ground, firmly set, with brass  
cap, marked and witnessed as described in the official  
record.

E. 0° 33' W., on a true line bet. secs. 31 and 32.  
Over level land, through very scattering timber.

53.70 Road, bears N. 20° E. and S. 20° W.  
Proportional distance.

39.88 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for reestablished 1/4 sec. cor. of secs.  
31 and 32, with brass cap mtd.

1/4  
S 31 | S 32  
1927

From which  
A black oak, 6 ins. diam., bears E. 54° E.,  
116 lbs. dist., mtd. 1/4 S 32 B F.

A black oak, 6 ins. diam., bears E. 24° 30' W.,  
72 lbs. dist., mtd. 1/4 S 31 B F.

79.75 Proportional distance.

Set an iron post, 3-ft. long, 2-ins. diam., 27 ins. in  
the ground, for reestablished cor. of secs. 29, 30,  
31 and 32, with brass cap mtd.

R 24 R R 6 E  
S 30 | S 29  
S 32 | S 32  
1927

From which  
A jack pine, 8 ins. diam., bears E. 45° 30' E.,  
173 lbs. dist., mtd. R 24 R R 6 E S 29 B F.

A black oak, 5 ins. diam., bears S. 54° E., 147  
lbs. dist., mtd. R 24 R R 6 E S 32 B F.

A black oak, 10 ins. diam., bears S. 64° W., 352  
lbs. dist., mtd. R 24 R R 6 E S 31 B F.



Dependent Recovery of the Subdivisional Lines.  
R. 24 N. R. 6 E.

Chains	A black oak, 4 ins. diam., bears N. 12° W., 238 lbs. dist., mtd. # 24 N R 6 E S 30 B F. Land, level.
	Soil, sandy, 3rd rate. Timber, black oak and jack pine.
	W. 69° 10' E., on a true line bet. secs. 29 and 32. Over level land, through scattering timber.
15.80	Road, bears NW. and SE.
36.00	Road, bears NE. and SW.
39.78	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 29 and 32, with brass cap mtd.
	From which N 1/4 S 29 1927
79.56	A black oak, 6 ins. diam., bears N. 5° E., 60 lbs. dist., mtd. 1/4 S 29 B F. A Norway pine, 8 ins. diam., bears S. 59° W., 102 lbs. dist., mtd. 1/4 S 32 B F. Also sold a Land, level. Soil, sandy, 3rd rate. Timber, black oak and jack pine.
39.94	From the cor. of secs. 29, 30, 31 and 32. S. 89° 34' W., on a true line bet. secs. 30 and 31. Over level land, through scattering timber. Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 30 and 31, with brass cap mtd. From which S 30 1/4 S 31 1927
	A jack pine, 9 ins. diam., bears N. 41° W., 25 lbs. dist., mtd. 1/4 S 30 B F. A jack pine, 7 ins. diam., bears S. 38° 30' W., 28

Dependent Recovery of the Subdivisional Lines,  
R. 24 N. R. 6 E.

75.20	1/4 in. dist., mtd. 1/4 S 31 B F. Road, bears N. and S.
75.48	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township, previously described. Land, level. Soil, sandy, 3rd rate. Timber, black oak and jack pine.
	From the cor. of secs. 29, 30, 31 and 32. N. 0° 22' E., on a true line bet. secs. 29 and 30. Over level land, through very scattering timber and light undergrowth. Proportional distance.
75.88	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 29 and 30, with brass cap mtd.
	From which S 30   S 29 1/4 1927
73.20	A white oak, 7 ins. diam., bears S. 88° E., 186 lbs. dist., mtd. 1/4 S 29 B F.
73.40	A black oak, 8 ins. diam., bears S. 80° E. Road, bears N. 80° W. and S. 80° E.
73.75	Leave level land, thence over rolling land. Enter timber, bears N. 80° E. and S. 80° E. Proportional distance. Set a concrete monument, 6 x 6 x 24 ins., 18 ins. in the ground, for reestablished cor. of secs. 19, 20, 29 and 30, with brass tablet mtd. From which S 24 N R 6 E S 29   S 20 S 30   S 29 1927
	A jack pine, 10 ins. diam., bears S. 5° E., 44 lbs. dist., mtd. # 24 N R 6 E S 29 B F.



Dependent Recovery of the Subdivisional Lines,  
T. 24 N., R. 6 E.

Chains	
79.55	A jack pine, 10 ins. diam., bears S. 62° 15' W., 99 lbs. dist., nkd. T 24 N R 6 E S 30 B T. A jack pine, 12 ins. diam., bears N. 7° 45' W., 34 lbs. dist., nkd. T 24 N R 6 E S 19 B T. Land, level and rolling. Soil, sandy, 3rd rate. Timber, jack pine and black oak. Undergrowth, young timber.
51.00	H. 69° 05' E., on a true line bet. secs. 20 and 29. Over gently rolling land, through timber and undergrowth. Leaves timber, bears N. and S. Undergrowth continues. Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 20 and 29, with brass cap nkd.
79.55	From which $\begin{array}{r} 55 \\ \times 1/4 \\ \hline 13.75 \\ \times 29 \\ \hline 398.25 \end{array}$ From the south leg of corner No. 12 of Power Line bears N. 1° 09' W., 7.62 chs. distant. A local corner, a wooden post, 4 x 4 x 24 ins. above ground, bears N. 6° 15' E., 69½ lbs. distant. This corner was established about 1909 by engineers of the Consumers Power Company, and was based on sec. corners reestablished by single proportional measurement on latitudinal lines. No bearing tree available. Rollins Lookout tower of U. S. Forest Service bears North, 7 chains distant. Road, bears N. and S. The cor. of secs. 20, 21, 28 and 29. Land, gently rolling. Soil, sandy, 3rd rate. Timber, jack pine and black oak. Undergrowth, scrub oak.
51.00	From the cor. of secs. 19, 20, 29 and 30. S. 89° 46' W., on a true line bet. secs. 19 and 30.

Dependent Recovery of the Subdivisional Lines,  
T. 24 N., R. 6 E.

Chains	
79.00	0-05 gently rolling land, through timber and light undergrowth. Road, bears S. 65° E. and N. 65° W.
79.00	Enter scattering timber, bears N. 60° W. and S. 60° E. Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs. 19 and 30, with brass cap nkd.
79.00	From which $\begin{array}{r} 55 \\ \times 1/4 \\ \hline 13.75 \\ \times 30 \\ \hline 412.50 \end{array}$ A black oak, 8 ins. diam., bears N. 80° 45' E., 68 lbs. dist., nkd. 1/4 S 19 B T. A black oak, 10 ins. diam., bears S. 56° W., 55 lbs. dist., nkd. 1/4 S 30 B T. Road, bears N. and S. Electric power transmission line, bears N. 55° E. and S. 55° W.
74.00	Road, bears N. and S.
74.55	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township, previously described. Land, gently rolling. Soil, sandy, 3rd rate. Timber, black oak, and jack pine. Undergrowth, young timber.
64.00	From the cor. of secs. 19, 20, 29 and 30. N. 1° 40' E., on a true line bet. secs. 19 and 20. Over rolling land, through timber and undergrowth. Electric power transmission line, bears N. 87° 45' E. and S. 87° 45' W.
11.20	Descend 70 feet over N. slope, edge bears N. and W. S. shore of Loud Basin on the An Sable River, bears N. and W. Thence across basin.
26.00	N. shore of Loud Basin, bears E. and W. Thence over level land, through cedar and tamarack swamp. Proportional distance.
79.90	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for reestablished 1/4 sec. cor. of secs.



Dependant Recovery of the Subdivisional Lines,  
R. 24 N., R. 6 E.

Chains	19 and 20, with brass cap nhd.	1/4 S 29 1/2 S 20
	From which	
	A cedar, 8 ins. diam., bears N. 62° E., 40 lbs. dist., nhd. 1/4 S 20 R T.	
	A cedar, 5 ins. diam., bears S. 70° 15' W., 37 lbs. dist., nhd. 1/4 S 19 B T.	
19-19	The true point for the cor. of secs. 17, 18, 19 and 20, which is marked by an iron pipe, 1 in. diam., 10 ins. above ground, set by engineers of the Consumers Power Company from an original bearing tree, now in existence. In place of the iron pipe, Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for reestablished cor. of secs. 17, 18, 19 and 20, with brass cap nhd. From which S 18 S 17 S 19 S 20	
	A fallen hemlock, 14 ins. diam., bears S. 60° W., 11 lbs. dist., nhd. R 6 R 24 B T. And a local bearing tree	
	A cedar stump, 16 ins. diam., bears N. 27° 15' E., 51 lbs. dist., nhd. R B T. And new bearing trees	
	A cedar, 4 ins. diam., bears N. 12° 15' E., 37 lbs. dist., nhd. R 24 R 6 R S 17 B T. A white pine, 8 ins. diam., bears S. 38° 30' E., 79 lbs. dist., nhd. R 24 R R 6 R S 19 B T. A Norway pine, 5 ins. diam., bears N. 79° 35' W., 62 lbs. dist., nhd. R 24 R R 6 R S 18 B T. A local corner, a wooden post, 4 x 4 x 16 in. above ground, bears N. 63° 19' W., 29 lbs. dist. Land, rolling and level, through cedar and tamarack swamp. Soil, sandy, 3rd rate, on upland; muck, 3rd rate, in	

Dependant Recovery of the Subdivisional Lines,  
R. 24 N., R. 6 E.

18-50	swamp. timber, cedar, black oak, jack pine, tamarack, balsam and white pine. Undergrowth, young timber and alder. N. 89° 57' E., on a true line bet. secs. 17 and 20. Over-level land, through cedar swamp. rolling land, through timber and undergrowth. Telephone line, bears N. and S.	
19-46	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness corner to the reestablished 1/4 sec. cor. of secs. 17 and 20, with brass cap nhd. S 17 W E S 20 W E 1927	
	From which A Norway pine, 5 ins. diam., bears N. 86° 30' W., 59 lbs. dist., nhd. W C 1/4 S 17 B T. A Norway pine, 16 ins. diam., bears S. 57° E., 37 lbs. dist., nhd. W C 1/4 S 20 B T.	
19-70	N. shore of a bay of Loud Basin on the An Sable River, bears NW. and SE. Thence over waters of Basin. Proportional distance.	
19-73	The true point for the reestablished 1/4 sec. cor. of secs. 17 and 20, falls in Loud Basin.	
19-80	The E. shore of bay, bears N. 20° W. and S. 30° E. Thence over level, wet land, through young timber and undergrowth.	
19-46	The cor. of secs. 16, 17, 20 and 21, falls in Loud Basin, level. Soil, muck, 3rd rate, in swamp; sandy, 3rd rate, on upland. Timber, cedar, poplar, Norway pine, white pine, tamarack. Undergrowth, young timber and alder.	
19-50	From the cor. of secs. 16, 18, 19 and 20, run a true line bet. secs. 16 and 19. S. 89° 51' W., on a true line bet. secs. 16 and 19. Over level land, through cedar and tamarack swamp. Leave swamp, bears N. and S. Thence over low, wet land; enter white pine timber.	