

On the 24th & 25th days of January A.D. 1889 in answer to a petition signed by Charles Titus, S. F. Jones John T Bayle, & Caroline Jones I surveyed the South East 1/4 of section 12 in the above mentioned town. The courses distances and areas appear on the plat on the opposite page. The corners are described as follows.

Corner No

- 1 A stone corner previously set
- 2 See corner No 17 Page 91
- 3 " " No 16 " 91
- 4 Found a stone corner claimed to be at the point of the original corner
- 5 Set a gray stone 9x12x23 inches with broken earthen around the top
- 6 At the intersection of the 4 lines set a Brown stone 9x13 with earthen around the top
- 7 See corner No 8 Page 211.
- 8 " " No 14 " 211
- 9 Set a stone 6x7x11. face side to the North with a cross cut on the North side
- 10 Set a post fr wh a Hemlock 6 Bears S 1° 30' E 9 l; Sugar 30 Bears N 5° W 23 l.
- 11 Set a cedar post with an old ax on the South side
- 12 See corner No. 3 Page 213.
- 13 Set a post from wh - Cedar 5 Bears N 48° 30' 7 1/2 l; Hem - 6 Bears N 65 1/2° W 6 lks
- 14 See corner No. 2 Page 213.

E. M. Hyde Co Surveyor