**MECOSTA COUNTY REMONUMENTATION PROGRAM**

**Corner approved by Peer Group on March 24, 1994**

**LAND CORNER RECORDATION CERTIFICATE**

**Filing Requirement of Act 74, Mich. P.A. 1970**

STATE OF MICHIGAN
COUNTY OF MECOSTA
RECEIVED FOR RECORD

'94 AUG -3 P1:38

Carl Waldron
REGISTER OF DEEDS

**Register of Deeds Stamp & File Number**

For corners in Mecosta (County)

| | Located in: | Corner Code # |
|---|---|---|
| 1. Public Land Survey Sec. | T 15 N R 10 W | C-13, Big Rapids Township |
| | T____ R____ | |
| | T____ R____ | |
| 2. Property Controlling | S____ T____ R____ | |
| in Section | S____ T____ R____ | |
| 3. Miscellaneous | S____ T____ R____ | |
| Property in Sec. | S____ T____ R____ | |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | | | | | | | | | | | | | |
| 2 | | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | |
| 3 | | | | | | | | | | | | | |
| 4 | | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | |
| 5 | | | | | | | | | | | | | |
| 6 | | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | |
| 7 | | | | | | | | | | | | | |
| 8 | | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | |
| 9 | | | | | | | | | | | | | |
| 10 | | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | |
| 11 | | | | | | | | | | | | | |
| 12 | | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | |
| 13 | | | | | | | | | | | | | |

I, Thomas H. Sage a field survey on April 2, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

**September 26, 1837, John Hodgson, Deputy Surveyor, GLO Notes, Volume 2, Page 223**
**Set Post**
**Pine 18" N57°W 34 links**
**Pine 16" N61°E 21 links**
**October 14, 1901, Lyman W. June, County Surveyor, Field Book No. 4, Pages 126-127, Record Book No. 1, Page 92**
**Original -- Two Original Bearing Tree Stumps -- Stake and Stones**
**October 22, 1906, Lyman W. June, County Surveyor, Field Book No. 7, Pages 158-159, Record Book No. 1, Page 143**
**Original Standard Corner - Stake and Stones**
**1965, George Blass, RLS**
**Found 3/4" x 3 foot Iron Bar**
**Red Oak 16" N54°E 64.37 feet**
**B. Oak 20" S35°E 120.89 feet**
**Northeast Corner, Section 6, T14N-R10W is 13.20 feet West (Witness notes do not mention what type of object was present. 13.20 feet is the GLO falling distance).**

**Continued on Back .....**

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

**Found Standard USFS Monument with Brass Cap on April 2, 1994 approximately 20" deep. I also recovered Mr. Blass's 1965 witnesses which fit the monument as follows:**
**Oak 20" with blaze N55°E 64.0 feet +\- to center of the tree**
**Oak 30" with blaze S35°E 121.0 feet +\- to the center of the tree**
**NOTE: There are nails under the bark. An attempt was made to recover the nails; but was unsuccessful.**
**I recovered Mr. Griffin's witnesses as follows:**
**White Oak 24" N50°E 47.31 feet Nail in Westside**
**Power Pole S31°E 80.91 feet Nail in Westside**
**White Oak 12" S41°W 83.88 feet Nail in Southside**
**White Pine 12" N33°W 87.58 feet Nail in Westside**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**Standard USFS Monument with Brass Cap**
**White Oak 24" N50°E 47.31 feet Nail in Westside**
**Power Pole S31°E 80.91 feet Nail in Westside**
**White Oak 12" S41°W 83.88 feet Nail in Southside**
**White Pine 12" N33°W 87.58 feet Nail in Westside**
**Mecosta Remonumentation Monument West 13.80 feet**

APPROVED BY MECOSTA CO. PEER GROUP
IN ACCORDANCE WITH P.A. 345 of 1990
James H. Knapp
CHAIRMAN
DATE MAR. 24, 1994

**Monument is accepted as a careful and faithful perpetuation of the position of the original corner.**

Signed by Thomas H. Sage Date MAY 10, 1994

Surveyor's Michigan License No. 33139

STATE OF MICHIGAN
THOMAS H.
SAGE
LAND SURVEYOR
NO.
LICENSED

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 25, 1971
REVISED MAY 20, 1975
REVISED JAN., 1983
ADAPTED FOR WORD PROCESSING MARCH, 1993