

**SURVEY &  
REMONUMENTATION**

**MECOSTA COUNTY REMONUMENTATION PROGRAM**

OCT 29 1998

CORNER APPROVED BY PEER GROUP ON August 14, 1998

STATE OF MICHIGAN  
COUNTY OF MECOSTA  
RECEIVED FOR RECORD

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE**

Filing Requirement of Act 74, Mich. P.A. 1970

'98 SEP 24 AM 10:01

For corners in

Mecosta  
(County)

Located in:  
Mecosta Twp

Corner Code #

1. Public Land Survey SEC 20 T 14N R 10W

E-7

2. Property Controlling S

in Section S

3. Miscellaneous S

Property in Sec. S

4. Lot No. \_\_\_\_\_ Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, James J. Keller, in a field survey on July 27 19 98, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

March 1, 1838, Abner E. Van Ness, Deputy Surveyor GLO, "Set post Cor of Sect. 16, 17, 20, & 21."  
8" Beech S37-1/2°E 7 Links (4.62')  
8" Hemlock S5°W 38 Links (25.08')

December 13, 1926, Wm Fargo, CP Co. Dwg #F-5618, "Accepted RR Iron & stone."  
10" Maple S26°W 75 Links (49.50')  
20" W. Oak N68-1/2°W 99-1/2 Links (65.67')

June 13, 1979, Norman L. Ochs, RLS #22439 (LCRC LI P487) "End 3/4" pipe."  
P. pole West 34.09'  
28" Maple S26°W 49.4'  
P. pole S58°E 54.26'  
10" R. Pine N43°E 47.34'

October 17, 1990, James J. Keller, RLS #10693 (FB 107-W P74) End 3/4" pinch top IP 1.0' deep.  
End 40d in P. pole N7-1-132 N87°W 34.05'  
End 40d NW sd 16" Red Pine N44°E 47.38'  
End 40d SW sd P. pole N71-132-B S53°E 54.21'  
End N85S cap & 40d in 40" Maple S28°W 49.33'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

July 27, 1998, James J. Keller, RLS #10693 (FB 138-W P58) End 3/4" Pinch top IP 14" deep.  
End 40d S sd P. pole N86°W 34.05'  
Set 60d SE sd 14" Red pine N46°E 47.10'  
End 40d SW sd P. pole S52°E 54.46'  
End N85S cap NW sd 38" Maple S31°W 49.40'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Accepted rusty pinch top 3/4" pipe & set Remonumentation Monument over it as best evidence of the position of the original corner.  
End 40d S sd P. pole & set PK nail & tag above N86°W 34.05'  
End 60d E set tag SE sd 14" Red Pine N46°E 47.10'  
End 40d SW sd P. pole & set PK nail & tag above S52°E 54.46'  
End N85S cap NW sd 38" Maple & set 60d E tag above S31°W 49.40'

Signed by

*James J. Keller*


Surveyor's Michigan license No. 10693

Date August 20, 1998

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7	19	20	21	22	23	24							
8													
9	30	29	28	27	26	25							
10													
11													
12	31	32	33	34	35	36							
13													

*James J. Keller*  
REGISTER OF DEEDS



FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN. 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1993

APPROVED BY MECOSTA CO. PEER GROUP  
IN ACCORDANCE WITH P.A. 345 OF 1990

*James J. Keller*  
CHAIRMAN  
DATE Aug. 14, 1998