

MECOSTA COUNTY REMONUMENTATION PROGRAM

CORNER APPROVED BY PEER GROUP ON JULY 8, 2009

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in MECOSTA (County)

Located in: BIG RAPIDS, TOWNSHIP

Corner Code #

Instrument 200900006571 OR Liber Page 105 289

1. Public Land Survey T. 15 N. R. 10 W. E - 12

200900006571

Filed for Record in MECOSTA COUNTY, MICHIGAN KAREN HAHN, REGISTER OF DEEDS 08-04-2009 At 09:08:11 am. REMON COR 17.00 OR Liber 105 Page 289 - 290

2. Property Controlling in Section S R

200900006571 REMONUMENTATION

3. Miscellaneous S R WILKINSON & REMONUMENTATION

Property in Sec. S R FEB 0 5 2010

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat SECTION

5. Private Claims

Table with columns A-M and rows 1-13. A dot is present in cell 12, 32.

I, James H. Carter, in a field survey in May 4, 09 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 1 corner, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1838 - GLO Deputy Surveyor Abner Van Ness set Qr. Sec. Post at 40 chains

(1) Ironwood 6 N12E 27, (2) Maple 8 S12E 13

1895 - Sept 21, - Lyman June Mecosta County Surveyor - W1/4 Sec 33 - Stake -

(3) Pine Stump 18 N82W 27, (4) Pine Stump 16 N76E 39.

1975 - Dec 18, - Douglas Hooth, Land Corner Recordation Certificate L - 1, P - 220 - Set 2" x 24" long iron pipe at proportionate distance and on line between the NW & SW Corners of Section 33.

(5) N70E - 12" Oak - 45.67', (6) Due East - 9" Maple - 15.64', (7) S23W - 9" Maple - 4.53', (8) N40W - 12" Tri Oak - 32.10'.

1978 - Nov 27, - Douglas Hooth, Land Corner Recordation Certificate L - 1, P - 473 - Monument not found - Reset monument (5/8" Steel Bar 2.5' long) using found witnesses recorded in L - 1, P 220

(5) N70E - 12" Oak - 45.67', (6) Due East - 9" Maple - 15.64', (7) S23W - 9" Maple - 4.53', (8) N40W - 12" Tri Oak - 32.10'.

1979- July 12, - Gerald Gray, Survey Certificate - L 10, P 758 - Found 1" Rod - (5) S20W - 10" Oak - 4.5', (6) S85E - Tw. Maple - 15.57', (8) N55W - 12" Tri Oak - 32.2'.

1984 - Feb 17, - Duane Wood, Survey Certificate L - 11, P 313 - Fnd. Iron Pipe - (3) N70E - 12" Oak - 45.67', (6) Due East - 9" Maple - 15.63', (7) S23W - 9" Maple - 4.53', (8) N40W - 12" Tri Oak - 32.10'.

2003 - June 9, - Mid. Mich. Eng. Certificate of Survey preliminary unrecorded - Fnd . 5/8" Iron Rod

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4" x 2.5' Re-Rod 6" under dirt surface 0.35' east of angle iron flush with ground and 9 ft. east of center of two-track. The angle iron appeared to mark the location of the steel bar set by L. Schaub. Also found 3/4" x 3.72' thin wall pipe (no written record) 0.8' west of angle iron. Note! Top of 3/4" rerod had been made flat by hammering to 1".

Accepted the 3/4" x 2.5' Re-Rod (5/8" x 2.5' Steel Bar) called for by D. Hooth as the position of the 1/4 corner common to sections 33 & 32.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set standard Mecosta County Remonumentation Monument at position of the 3/4" x 2.5' Re-Rod and is accepted as the best available evidence of the position of the quarter corner common to sections 33 & 32. Set monument (6-18-09)


N 38 E - 38.98' - Re-Mon Tag & Nail in 17" Twin Red Oak

S 86 E - 15.52' - Re-Mon Tag & Nail in 19" Twin Red Oak (6)

N 75 W - 35.02' - Re-Mon Tag & Nail in 9" R. Oak

N 38 W - 30.06' - Re-Mon Nail & Tag in 16" Tri R Oak (8)

Center of Two - Track 8 +/- ft. West



Signed by James H. Carter Date July 10, 2009

Surveyor's Michigan License No. P.S. 33973

APPROVED BY MECOSTA CO. PEER GROUP IN ACCORDANCE WITH P.A. 345 of 1990

James J. Knapp CHAIRMAN DATE July 8, 2009

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

REVISED OCT., 1995