

**SURVEY &
REMONUMENTATION**

FEB 16 2006

SECTION

MECOSTA COUNTY REMONUMENTATION PROGRAM

Corner approved by the Peer Group on April 29, 2005

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in MECOSTA (County) Located In: _____ Corner Code # _____

Instrument 200500005029 OR Liber Page 103 490

- 1. Public Land Survey T 14N R 10W F-5
- T R
- T R
- T R
- T R
- 2. Property Controlling S
- In Section S
- 3. Miscellaneous S
- Property in Sec. S

200500005029
Filed for Record in
MECOSTA COUNTY, MICHIGAN
JOANNE BROWN
05-27-2005 At 08:04:35 AM.
REHON COR 14.00
OR Liber 103 Page 490 - 490

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3	7	8	9	10	11	12							
4	18	17	16	15	14	13							
5	19	20	21	22	23	24							
6	30	29	28	27	26	25							
7	31	32	33	34	35	36							


I, Thomas H. Sage, in a field survey on January 8, 2003, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
Position was not Established by GLO
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
On January 8, 2003
I Set 1/2" Iron with Cap #33139 on a straight line and even split between E-5 and G-5.
N10°W 6.38' 14" Pine Set Nail & Tag #33139 E. side
N70°E 17.73' 10" Pine Set Nail & Tag #33139 N. side
S70°E 8.61' 14" Pine Set Nail & Tag #33139 SW. side
S45°W 31.66' 16" Pine Set Nail & Tag #33139 NW. side
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

On May 9, 2005, I set a Remonumentation Monument over my Iron as a Careful and Faithful Perpetuation of the Position of the Corner.

- N10°W 6.38' 14" Pine Set Remon Tag Above Nail & Tag #33139 E. side
- N70°E 17.73' 10" Pine Set Remon Tag Above Nail & Tag #33139 N. side
- S70°E 8.61' 14" Pine Nail & Tag #33139 SW. side
- S45°W 31.66' 16" Pine Nail & Tag #33139 NW. side



Signed by _____ Date MAY 10 2005
Surveyor's Michigan License No. 33139

APPROVED BY MECOSTA CO. PEER GROUP
IN ACCORDANCE WITH P.A. 948 of 1990

James J. Knapp
DATE: Apr. 29, 2005

2005 Grant