

John Miletics, R L S. # 25859
 Project Number 81-080 December 5, 1981
 Found 5/8" Bar
 #3 Twin Maple N81°W 39 82'
 #6 8" Oak N45°W 27 72'
 #7 8" Oak S20°E 32 80'

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner

I found a 1" x 38" Rod, painted on bottom and with a 1/4" diameter top, 12"± below grade. No apparent North and South occupation. An East and West Deer Fence (North fence of 2 fences that are 14'± apart) 10'± South. The centerline of a two-track which bears N40°±E 34'± is East The condition of the witnesses are as follows: #1 and #2 gone, #3 and #4 in good condition, #5 gone, #6 stump hole of 8" diameter downed tree N46°W 27 5', #7 White Oak inside deer enclosure may be this witness

Part C: Field Evidence of Perpetuation or Monumentation of Corner

I removed the Rod and set a 4" diameter Harrison Cast Iron Monument 30" long marked "County Surveyor #22439" to project 4"± above grade and placed stones around monument as a careful and faithful perpetuation of the position of the original Section corner

#3 22" Black Oak N78°W 38 73'
 #4 18" White Oak S85°W 59 32'
 16" Black Oak N33°W 10 88'
 24" Black Oak (with blaze) S62°W 7 55'
 18", 28" Twin Black Oak (with blaze) N42°E 9 59'
 4" White Pine N85°E 24 92'

Set 40d nail with tag in North side
 Set 40d nail with tag in North side
 Set 40d nail with tag above overgrown nail in NE side
 Set 40d nail with tag in North side
 Set 40d nail with tag above overgrown nail in NW side
 Set 40d nail with tag in North side

Date of Observation	Latitude	Longitude	Datum and Adjustment Year	Epoch Date
09-26-2017	43°36'45 502"	(w)85°34'58 281"	NAD 83 2011	2010

Method for coordinate determination The Geodetic Coordinates were determined by RTK GPS measurement from an adjusted base point The base point was determined by static GPS observation, and verified by RTK GPS measurement from a separate adjusted base point.

Disclaimer on accuracy of values reported relative to their use 0 01 seconds of arc

I, Norman L. Ochs, in a field survey on September 26, 2017, certify under the requirements of the State Survey and Remonumentation Act, 1990 PA 345, MCL 54 261 to 54 279, and the Corner Recordation Act, 1970 PA 74, MCL 54 201 to 54 210d, that the corner identified and described hereon has been perpetuated or monumented as described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan

Norman L. Ochs January 9, 2018

Norman L. Ochs

Date January 9, 2018

Professional Surveyor's License No : 22439

P O Box 35, White Cloud, Michigan 49349

I, Norman L. Ochs, state that the corner identified and described hereon and perpetuated or monumented as described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on October 25, 2017 and is accepted for filing in the Newaygo County Remonumentation Program

Norman L. Ochs January 9, 2018

Norman L. Ochs

Date January 9, 2018

Professional Surveyor's License No : 22439