

**SURVEY &
REMONUMENTATION**

APR 04 1996

1995 Newaygo County Remonumentation Project

COMMISSION

**LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT of Act 74, Mich. P.A. 1970**

VOL. **1** PAGE **194**

NEWAYGO COUNTY

For corners in
Newaygo _____
(County)

Located in: _____ Corner Code #

- Public Land Survey
T 15N R 11W
T _____ R _____
T _____ R _____
T _____ R _____
- Property Controlling
in Section S _____ T _____ R _____
S _____ T _____ R _____
- Miscellaneous
Property in Sec. S _____ T _____ R _____
S _____ T _____ R _____

68 FEB 21 07 9 '92

Marlene Toogood


Register of Deeds Stamp & File Number

- Lot No. _____, Recorded Plat _____
- Private Claims _____

I, Norman L. Ochs, in a field survey on July 24, 1995, do hereby certify that under requirements of P. A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

Note: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

N.E. Corner, Section 26, Norwich Twp., Newaygo Co., MI



A. DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES AND/OR SUBSEQUENT RESTORATION:

G.L.O. Milton Nye 1856
9" Beech N88½°W 7Lks (4.62)'#1
6" Beech S12°W 17Lks (11.22)'#2

William M. Jacques (Co. Surveyor)
Book 24 Pg. 26 April 21, 1912
16" Pine S69 ½°E 15½' #3
20" Pine N30°E 13' #4
Measured 39.85 ch (2630.10 ft) from the N. ¼ Cor. to the N.E. Cor. of Sec. 26

NCRC Sheet Iron
24" R. Oak S01°W 19.3' #5
Pine Stp. N75°E 17.9' #7
Pine Stp. N38°E 15.7' #4
8" T. Oak S87°E 29.6' #6

NCRC Sheet
Measured 2470.66 ft from the N. ¼ Cor. to the N.E. Cor. of Sec. 26 and
Measured 2620.20 ft from the N.E. Cor. to the E. ¼ Cor. of Sec. 26

B. DESCRIPTION OF CORNER EVIDENCE FOUND AND/OR METHOD APPLIED IN RESTORING OR REESTABLISHING CORNER:

Found a 1½" iron rod that fit witnesses by William M. Jacques from 1912 and measured 2466.69 ft from the N. ¼ Cor. to the N.E. Cor. of Sec. 26 and measured 2608.68 ft from the N.E. Cor. to the E. ¼ Cor. of Sec. 26 and the condition of the recorded witnesses are: #1 and #2 gone, #3 and #4 fd. remains of stump, #5 and #6 good condition, #7 gone.

C. DESCRIPTION OF MONUMENT FOR CORNER AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATING THE POSITION OF THE CORNER:

Removed 1½" iron rod and set a 4" dia. Harrison cast iron monument 20" long marked "County Surveyor" as a substantial marker for the section corner and is accepted as a careful and faithful reestablishment of the original corner.

- 28" R. Oak S08°W 20.25' Spike in East side of tree. #5
- 14" Tri. R. Oak S81°E 29.67' Spike in South side of tree. #6
- 3" R. Oak N18°W 25.42' Spike in East side of tree.
- 4" Maple N37°E 15.85' Spike in West side of tree.

Signed by Norman L. Ochs Date September 11, 1995

Surveyor's Michigan License No. 22439

Form approved by Michigan State Board of Land Surveyors, Jan 28, 1971
Revised May 14, 1975
Revised Jan., 1983

Approved by Peer Review Group On September 12, 1995
Norman L. Ochs, County Representative.

N.L.O.

