

2003 Newaygo County Remonumentation Project

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Newaygo
(County)

Located in: Corner Code #

Corner Code #

- | | | | | |
|----|------------------------------------|---------------------|---|------|
| 1. | Public Land Survey | | T ¹⁴ <u>N</u> R ¹¹ <u>W</u> | H-11 |
| | | | T <u>N</u> R <u>R</u> W | |
| | | | T <u>N</u> R <u>R</u> W | |
| | | | T <u>N</u> R <u>R</u> W | |
| 2. | Property Controlling
in Section | S | T <u>N</u> R <u>R</u> W | |
| | | S | T <u>N</u> R <u>R</u> W | |
| 3. | Miscellaneous
Property in Sec. | S | T <u>N</u> R <u>R</u> W | |
| | | S | T <u>N</u> R <u>R</u> W | |
| 4. | Lot No. _____, | Recorded Plat _____ | | |
| 5. | Private Claims _____ | | | |

LINDA M. LANDHEER
NEWAYGO COUNTY
REGISTER OF DEEDS OFFICE
9 MAR 2024 2:09:04 PM
RECEIVED & RECORDED

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							

I, Norman L. Ochs, in a field survey on June 26, 2003, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 2, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

Note: Not more than 2 corners, all in the same town and range, may be Recorded on this certificate.

Quarter corner common to Section's 27 and 34, Goodwell Township, Newaygo County Michigan

A. DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES AND/OR SUBSEQUENT RESTORATION:

NO SUBSEQUENT EVIDENCE FOUND

G.L.O
James Mullett, 1837

Set $\frac{1}{4}$ post

#1 8" W. Oak N47°W 23 links (15.18')

#2 8" W. Oak N80°E 10 links (6.6')

B. DESCRIPTION OF CORNER EVIDENCE FOUND AND/OR METHOD APPLIED IN RESTORING OR REESTABLISHING CORNER:
1. 10' x 10' concrete pad 2. 10' x 10' concrete pad 3. 10' x 10' concrete pad 4. 10' x 10' concrete pad 5. 10' x 10' concrete pad 6. 10' x 10' concrete pad 7. 10' x 10' concrete pad 8. 10' x 10' concrete pad 9. 10' x 10' concrete pad 10. 10' x 10' concrete pad 11. 10' x 10' concrete pad 12. 10' x 10' concrete pad 13. 10' x 10' concrete pad 14. 10' x 10' concrete pad 15. 10' x 10' concrete pad 16. 10' x 10' concrete pad 17. 10' x 10' concrete pad 18. 10' x 10' concrete pad 19. 10' x 10' concrete pad 20. 10' x 10' concrete pad 21. 10' x 10' concrete pad 22. 10' x 10' concrete pad 23. 10' x 10' concrete pad 24. 10' x 10' concrete pad 25. 10' x 10' concrete pad 26. 10' x 10' concrete pad 27. 10' x 10' concrete pad 28. 10' x 10' concrete pad 29. 10' x 10' concrete pad 30. 10' x 10' concrete pad 31. 10' x 10' concrete pad 32. 10' x 10' concrete pad 33. 10' x 10' concrete pad 34. 10' x 10' concrete pad 35. 10' x 10' concrete pad 36. 10' x 10' concrete pad 37. 10' x 10' concrete pad 38. 10' x 10' concrete pad 39. 10' x 10' concrete pad 40. 10' x 10' concrete pad 41. 10' x 10' concrete pad 42. 10' x 10' concrete pad 43. 10' x 10' concrete pad 44. 10' x 10' concrete pad 45. 10' x 10' concrete pad 46. 10' x 10' concrete pad 47. 10' x 10' concrete pad 48. 10' x 10' concrete pad 49. 10' x 10' concrete pad 50. 10' x 10' concrete pad 51. 10' x 10' concrete pad 52. 10' x 10' concrete pad 53. 10' x 10' concrete pad 54. 10' x 10' concrete pad 55. 10' x 10' concrete pad 56. 10' x 10' concrete pad 57. 10' x 10' concrete pad 58. 10' x 10' concrete pad 59. 10' x 10' concrete pad 60. 10' x 10' concrete pad 61. 10' x 10' concrete pad 62. 10' x 10' concrete pad 63. 10' x 10' concrete pad 64. 10' x 10' concrete pad 65. 10' x 10' concrete pad 66. 10' x 10' concrete pad 67. 10' x 10' concrete pad 68. 10' x 10' concrete pad 69. 10' x 10' concrete pad 70. 10' x 10' concrete pad 71. 10' x 10' concrete pad 72. 10' x 10' concrete pad 73. 10' x 10' concrete pad 74. 10' x 10' concrete pad 75. 10' x 10' concrete pad 76. 10' x 10' concrete pad 77. 10' x 10' concrete pad 78. 10' x 10' concrete pad 79. 10' x 10' concrete pad 80. 10' x 10' concrete pad 81. 10' x 10' concrete pad 82. 10' x 10' concrete pad 83. 10' x 10' concrete pad 84. 10' x 10' concrete pad 85. 10' x 10' concrete pad 86. 10' x 10' concrete pad 87. 10' x 10' concrete pad 88. 10' x 10' concrete pad 89. 10' x 10' concrete pad 90. 10' x 10' concrete pad 91. 10' x 10' concrete pad 92. 10' x 10' concrete pad 93. 10' x 10' concrete pad 94. 10' x 10' concrete pad 95. 10' x 10' concrete pad 96. 10' x 10' concrete pad 97. 10' x 10' concrete pad 98. 10' x 10' concrete pad 99. 10' x 10' concrete pad 100. 10' x 10' concrete pad

I set a 4" diameter Harrison cast iron monument 30" long marked "County Surveyor #22439" at the intersection of remnants fence to South and East. The corner is online $\pm$ with remnants fence to the South. The corner is online $\pm$ with remnants fence to the East. No apparent occupation to North or West. The condition of the witnesses is as follows: #1 and #2 gone.

C. DESCRIPTION OF MONUMENT FOR CORNER AND ACCESSORIES ESTABLISHED TO PERPETUATE, LOCATING THE POSITION OF THE CORNER:

I set a 4"x30" Harrison monument marked "County Surveyor #22439" at the intersection of remnants fence to the South and East, as a substantial marker for the quarter corner and is accepted as a careful and faithful reestablishment of the position of the original quarter corner.

8" Maple (blazed) N27°E 28.51' ✓
 8" 8" Twin Black Oak (blazed) S47°E 15.89'
 6" Maple (blazed) S11°W 32.42'
 10" Black Oak (blazed) N23°W 36.00' ✓

Signed by Norman L. Ochs
Norman L. Ochs

Date July 30, 2003

Surveyor's Michigan License No. 22439

