



DELIVERED TO NEWAYGO CO.
01/19/2018 9:57:37 AM



STEWART K. SANDERS
NEWAYGO COUNTY REGISTER OF DEEDS
RECEIVED AND RECORDED
01/19/2018 10:42:08 AM

Land Corner Recordation Certificate
2017 Annual Grant Agreement
Authority: MCL 54.205 and R54.202

247

VOL. 8

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 - 54.210d and 2016 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Newaygo County

Corner Type	Survey Township	Corner Code	Goodwell Township												
			A	B	C	D	E	F	G	H	I	J	K	L	M
Original Public Land Survey Corner - MCL 54.202(g) - MCL 54.262(g)	T 14N R 11W	L07	2	6	5	4	3	2	1	2	3	4	5	6	7
	T		3												
	T		4	7	8	9	10	11	12	4					
	T		5												
Property Controlling Corner - MCL 54.202(i) - MCL 54.262(h)	T		6	18	17	16	15	14	13	6					
	T		7												
	T		8	19	20	21	22	23	24	8					
	T		9												
Protracted Public Land Survey Corner - MCL 54.202(k) - MCL 54.262(i)	T		10	30	29	28	27	26	25	10					
	T		11												
	T		12	31	32	33	34	35	36	12					
	T		13												

One Quarter Corner common to Sections 13 and 24, T14N R11W, Goodwell Township, Newaygo County, Michigan.

Part A: Corner History

- GLO
J.H. Mullett, November 22, 1837
Set quarter section post
#1 18" Beech S81°E 27 links (17.82')
#2 8" Beech N33°E 15 links (9.9')

Newaygo County Road Commission Sheet
1950's±
#3 Corner Post N5°W 28.9'

Robert L. Wetherell, R.L.S. # 24624
I did not recover any monument at this location. I found the East 1/8 post per the Newaygo County Road Commission witness sheet, E1/8 post on North Section line of Section 24, Steel Post with the following witnesses:
6" White Oak N30°W 25.0', Tree S5°E 25.6'. I set the corner by doubling over the distance from the found East 1/8 post to the Northeast Section Corner (1321.94' respectively).
#4 4"-6" Twin Maple N49°E 57.84' 60d spike in NW side
#5 8" White Oak N16°W 28.49' 60d spike in West side
#6 7" White Pine S32°E 104.03' 60d spike in West side
#7 6" White Pine S38°W 136.85' 60d spike in West side