



VOL. 8 205



STEWART K. SANDERS
NEWAYGO COUNTY REGISTER OF DEEDS
RECEIVED AND RECORDED
01/26/2017 3:51:19 PM

Land Corner Recordation Certificate
2016 Annual Grant Agreement
Authority: MCL 54.205 and R54.202

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2016 State Survey and Remuneration Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Newaygo County

Corner Type	Survey Township	Corner Code	Goodwell Township												
			1	A	B	C	D	E	F	G	H	I	J	K	L M
Original Public Land Survey Corner • MCL 54.202(g) • MCL 54.262(g)	T 14N R 11W	L09	1	6	5	4	3	2	1						
	T	R	2												
	T	R	3												
	T	R	4	7	8	9	10	11	12						
	T	R	5												
Property Controlling Corner • MCL 54.202(i) • MCL 54.262(h)	T	R	6	18	17	16	15	14	13						
	T	R	7												
	T	R	8	19	20	21	22	23	24						
	T	R	9												
Protracted Public Land Survey Corner • MCL 54.202(k) • MCL 54.262(i)	T	R	10	30	29	28	27	26	25						
	T	R	11												
	T	R	12	31	32	33	34	35	36						
	T	R	13												

One Quarter Corner common to Sections 24 and 25, T14N R11W, Goodwell Township, Newaygo County, Michigan.

Part A: Corner History

GLO

J.H. Mullett, November 12, 1837
A 8" Pine for quarter section post

Robert A. Griffin, R.L.S. # 13584
LCRC # 450 October 31, 1977

Found a railroad rail 18" long in the East and West road in line with the old fence North.

Set 5" square x 36" concrete monument with brass cap

- #1 1" Pipe N5°E 30.16'
- #2 4" square x 7' Post North 32.82'
- #3 6" Red Oak S33°W 57.45'
- #4 5" White Pine N28°W 69.18'

Robert L. Wetherell, R.L.S. # 24624
On witness card dated May 1996

Found USFS Concrete Monument

- #2 Wood Post North 32.83'
 - #3 10" Red Oak S33°W 57.45'
 - #5 14" Red Oak N27°W 20.56'
 - #6 12" White Pine S25°E 21.12'
- Nail and Washer
Dock Spike
Nail in West side
Nail in East side