

Part A: Continued

James G. Knapp, R.L.S. # 25853
Mecosta County Remonumentation LCRC
Recorded in Liber 104, Page 153 November 5, 2005
Found ¾" Iron Pipe with cap "JEP 19305" driven in a 1½" Well
Point, surrounded with stones, buried 2" below gravel road
surface, in center of Newcosta Avenue (20' gravel – South and
10' trail- North) and 4' South of center of 3 Mile (22' gravel –
West).
Drove a standard Mecosta County Remonumentation Monument
over the ¾" Iron Pipe, inside the Well point, buried 8" deep
#10 10" Red Pine Az 58° (N58°E) 54.04' set 60d spike & tag in
NW side
#5 24" White Oak Az 132° (S48°E) 34.83' set 60d spike & tag in
NE side
#3 Power Pole Az 252° (S72°W) 86.00' found pk nail in
North side
#11 34" White Pine Az 354° (N6°W) 77.72' set 60d spike & tag
in East side

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner(s)

I found the Mecosta County Remonumentation Monument 2" Pipe with brass cap #25853 (James G. Knapp) 1' below grade and at the
apparent point of intersection of gravel roads to the South and West. A two track road runs North from the corner position. The condition
of the witnesses are as follows: #1 and #2 gone, #3 in good condition, #4 gone, #5 in good condition, #6 gone, #7 thru #11 in good
condition.

Part C: Field Evidence of Perpetuation or Monumentation of Corner(s)

I accepted the found Mecosta County Remonumentation Monument 2" Pipe with brass cap #25853 (James G. Knapp) 1' below grade,
as a careful and faithful reestablishment of the position of the original Section corner.

#3 Power Pole S64°W 85.94' Found mag nail in North face
#5 26" Black Oak S54°E 34.63' Found nail in Northeast face
#7 15" Twin Black Oak S41°W 57.16' Set nail and tag in Southeast face
#10 13" Red Pine N56°E 54.09' Found nail and tag in North face
#11 30" White Pine N11°W 77.81' Found nail and tag in East face


Date of Observation	Latitude	Longitude	Datum and Adjustment Year	Epoch Date
10-05-2015	43°35'53.204"	85°33'45.384"	NAD 83, 2011	2010

Method for coordinate determination: Geodetic coordinates were determined by RTK GPS measurement from an
adjusted base. The base position was set using Static GPS observations.

Disclaimer on accuracy of values reported relative to their use: 0.01 seconds of arc.

I, Norman L. Ochs, in a field survey on October 5, 2015, certify under the requirements of the State Survey and
Remonumentation Act, 1990 PA 345, MCL 54.261 to 54.279, and the Corner Recordation Act, 1970 PA 74, MCL
54.201 to 54.210d, that the corner(s) identified and described hereon has been perpetuated or monumented as
described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan.

Norman L. Ochs 2/2/2016
Norman L. Ochs Date
Professional Surveyor's License No.: 22439
Newwaygo Engineering & Survey, P.O. Box 35, White Cloud, MI 49349



I, Norman L. Ochs, state that the corner(s) identified and described hereon and perpetuated or monumented as
described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on October 13, 2015
and is accepted for filing in the Newwaygo County Remonumentation Program.

Norman L. Ochs 2/2/2016
Norman L. Ochs Date
Professional Surveyor's License No.: 22439

