

Part A: Continued

James J. Keller, R.L.S. # 10693
Survey Recorded in Liber 12, Page 421 November 19, 2001
Found 1/2" Rebar, 6" deep and shows a distance of 2708.08' to
the North Corner and 2627.22' to the West 1/4 Corner Section 30,
Mecosta Twp.
#6 14" Red Oak N31°E 92.15' found 30d SE side
#8 Triple White Oak N75°E 87.38' found 30d South side
#4 Power Pole S42°W 55.10' found 30d SE side

James G. Knapp, R.L.S. # 25853
Mecosta County Remonumentation LCRC recorded in Liber 104,
Page 168
November 5, 2005
Found 5/8" x 17" Rebar, 6" below gravel road surface, excavated
36" found no other evidences of monumentation, in center of 2 Mile
road (18" gravel West) and 30 feet Wets of Newcosta Avenue (20'
gravel) however it is in line with center beyond curve to the North
Placed a standard Mecosta County Remonumentation monument
at location of the 5/8" Rebar buried 7" deep.
#6 20" White Oak Az 28° (N28°E) 91.72' found double head
nail S side
#8 12" Quad White Oak Az 74° (N74°E) 87.38' found spike S side
#5 4" diameter xx 4' - 4" high Iron Pipe Fence Post Az 232°
(S52°W) 44.90'
#9 14" Cherry Az 264° (S84°W) 105.26' set spike with tag in
North side

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner(s)

I found the Mecosta County Remonumentation Monument, 2" x 36" Pipe with brass cap marked #25853 (James M. Knapp), 6" below road surface in extended intersection of gravel roads to the North and West, and asphalt road to Southeast. The condition of the witnesses are as follows: #1 thru #4 gone, #5 did not check, #6 in good condition, #7 gone, #8 in good condition, #9 did not look for, #10 in good condition.

Part C: Field Evidence of Perpetuation or Monumentation of Corner(s)

I accepted the found Mecosta County Remonumentation Monument, 2" x 36" Pipe with brass cap marked #25853 (James M. Knapp), 6" below road surface, as a careful and faithful reestablishment of the position of the original Section corner.

#6 24" Red Oak N23°E 92.08' Set nail and tag over found nail in Southeast face
#8 14" Quad White Oak N68°E 87.44' Set nail and tag over found nail in South face
Power Pole S77°E 151.42' Set nail and tag in North face
Power Pole N52°W 46.89' Set nail and tag in Southwest face
21" Cherry S69°W 81.76' Set nail and tag over found tag in North face

Date of Observation	Latitude	Longitude	Datum and Adjustment Year	Epoch Date
10-05-2015	43°35'01.086"	(w)85°33'42.122"	NAD 83, 2011	2010

Method for coordinate determination The Geodetic Coordinates were determined by RTK GPS measure from two separate adjusted base points. The base points were determined by static GPS observation, and adjusted using OPUS rapid static.

Disclaimer on accuracy of values reported relative to their use: 0.01 seconds of arc


I, Norman L. Ochs, in a field survey on October 5, 2015, certify under the requirements of the State Survey and Remonumentation Act, 1990 PA 345, MCL 54.261 to 54.279, and the Corner Recordation Act, 1970 PA 74, MCL 54.201 to 54.210d, that the corner(s) identified and described hereon has been perpetuated or monumented as described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan.

Norman L. Ochs 2/2/2016
Date

Norman L. Ochs

Professional Surveyor's License No.: 22439

Newaygo Engineering & Survey, P.O. Box 35, White Cloud, MI 49349



I, Norman L. Ochs, state that the corner(s) identified and described hereon and perpetuated or monumented as described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on October 13, 2015 and is accepted for filing in the Newaygo County Remonumentation Program.

Norman L. Ochs 2/2/2016
Date

Norman L. Ochs

Professional Surveyor's License No.: 22439

