


SURVEY &
REMONUMENTATION

SEP 11 2007

SECTION

OSCODA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970* L C 8 - 1 3 1 *



For corners in

OSCODA
(County)

Located In: Corner Code #

1. Public Land Survey

T26N

R1E

J-5

2. Property Controlling

S

T

R

J-5

3. Miscellaneous

S

T

R

J-5

Property in Sec.

S

T

R

J-5

4. Lot No. , Recorded Plat
5. Private Claims

APPROVED

County Remonumentation
Peer Review Group

NC 25 AUG 07

JERI WINTON

OSCODA COUNTY

REGISTER OF DEEDS

08/29/2007 10:09:15AM

FEE: \$14.00

PAGES: 1 RCPT#: 5761

LC8-131 CORNER RECORDATION

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2								
3													
4	7	8	9	10	11	12							
5													
6	13	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Marvin E. Myers, P.S., in a field survey on June 4, 20 07, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-5 Quarter Section Corner common to Sections 11 & 14 of T.26N.-R.1E.

1839 GLO William R. Coon Deputy Surveyor

Mon.- Set quarter Section post

Wit: Spr Pine 10" N20°E 11 lks (7.26)

Spr Pine 8" S20°W 52 lks (34.32)

1912 Oscoda County Surveyor C.O. Seeley

Mon.- North from ¼ post between Sec 11 and 14

Wit: Left swamp N01°40"E 10 chains

1912 Oscoda County Surveyor C.O. Seeley

Mon.- Set ¼ post between Sec 11-14

Wit: NBT Tamarack 7" S59 ½°E 57 lks (37.62)

1937 USGLO Dependent Resurvey Guy R. Veal Cadastral Eng.

Mon.- Proportionate distance; there is no remaining

evidence of the original post or bearing trees.

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins.

in the ground, for ¼ sec. cor., with brass tablet, 3 ½ ins.

diam., 3 in. stem, embedded in top and mkd.

Wit: A white pine; 24 ins. diam., bears N. 87° E., 202 lks.

(133.32) dist., mkd. ¼ S 11 B T.

A balsam. 7 ins. diam., bears N. 62° W., 100 ½ lks.

(66.33) dist., mkd. ¼ S 14 B T.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-5 Quarter Section Corner common to Sections 11 & 14 of T.26N.-R.1E.

Found USGLO monument in good condition. Found no existing witnesses of record. Accepted USGLO monument as a careful and faithful reestablishment of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
J-5 Quarter Section Corner common to Sections 11 & 14 of T.26N.-R.1E.

Mon - Left USGLO monument in place and placed two spikes along side for future magnetic detection

Wit: S52°W 12.81' Set N&T S side 3" Balsam

S88°E 11.63' Set N&T N side 4" Balsam

S39°E 16.29' Set N&T W side 3" Balsam

N37°W 29.10' Set N&T E side 4" Balsam

North 2'± Set carsonite post



Signed by Marvin E. Myers

Surveyor's Michigan License No. 31600

Date

August 21, 2007

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 23, 1971

REVISED MAY 14, 1973

REVISED JAN., 1993

ADAPTED FOR WORD PROCESSING MARCH, 1995