



LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

OSCODA COUNTY, BIG CREEK TOWNSHIP
FOR CORNERS OF--

LOCATED IN-- Sec 3

CORNER CODE NUMBER

1. PUBLIC LAND SURVEY T. 26 N. 1 E. W.

H-3; G-3; G-2

2. PROPERTY CONTROLLING IN SECTION T. N. S. R. E. W.

H-1

3. MISCELLANEOUS PROPERTY IN SECTION T. N. S. R. E. W.

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

Liber 1
Page 233

FILED

At 9:18 AM on 11-14-79

Osceola County, Michigan

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Edwin J McCombs, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on in May, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

H-3 Found Resurvey GLO monument

G-3 Found Resurvey GLO monument for witness point

G-2 Found Resurvey GLO monument

H-1 Found Resurvey GLO monument

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-3 6" red pine S 45°E 22.82'
15" oak N 26°E 13.57'
15" oak N 80°W 38.71'
6" red pine S 10°W 28.42'

G-2 8" spruce N 25°E 32.92'
12" spruce N 15°W 30.10'
20" spruce East 18.56'

G-3 Set Re-rod
10" Jack pine S 85°E 31.75'
15" oak N 20°W 34.77'
8" Jack pine S 25°W 14.67'

H-1 20" red pine N 50°E 46.48'
10" oak N 30°W 39.99'
6" oak S 50°W 38.90'
15" oak S 40°E 40.13'
GLO monument for T27N, R1E East 11.12'

SIGNED BY Edwin J McCombs

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 10696

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

DATE

APPROVED AND SIGNED BY

CHIEF OF SURVEY PARTY

DATE

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET