

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Oscoda _____
(County)

Located In:

Corner Code #

1. Public Land Survey

T	26N	R	2E	A - 10
T		R		
T		R		
T		R		
S		R		
S		R		
S		R		
S		R		

2. Property Controlling
in Section

S

3. Miscellaneous

S

Property in Section

S

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Marvin E. Myers, in a field survey on June 5, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, re-monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO-L. Clawson May 1839

Mon-Post

WIT: 7" Spruce S51°W 22 lks.

5" Spruce N68½°W 10 lks.

Randall Sept. 1, 1883

Remarkd post fd. original & verified

by measurement to BT down & decaying

WIT: 5" Spruce N68½°W 10 lks.

GLO-C. Veal Oct. 1935

Mon-Fd. 4"x4"x24" Wood Post

at fence intersection set

at this point Conc. Mon.

with Brass Tablet

WIT: 6" J.Pine N50°E 71 lks.

8" J.Pine S25 3/4°W 67 lks.

C E-W road North 1.00 chs.

LCRC L.3, pg.258

Gary Wilson Sept. 21, 1992

Mon-Fd. GLO Mon.

80' South of E-W Co. Rd. &

29' W. of Sand Trail

WIT: 10" B.Oak N18°E 134.73'

½" Bar & Cap S70°E 135.00'

10" B.Oak N02°W 136.65'

A	B	C	D	E	F	G	H	I	J	K	L
2	6	5	4	3	2	1					
3											
4	7	8	9	10	11	12					
5											
6	18	17	16	15	14	13					
7											
8	19	20	21	22	23	24					
9											
10	30	29	28	27	26	25					
11											
12	31	32	33	34	35	36					
13											

APPROVED

County Remonumentation
Peer Review Group

NCC/31/2025
JULY

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon-US GLO Conc. Mon. with iron along side

WIT: 80'± South of E-W road

29'± West of Sand Trail Road

Fd. ½" Bar & Cap 25881 West 60.00'


Fd. ½" Bar & Cap 25881 S70°E 135.00'

Fd. 10" B.Oak N18°E 134.73'

Fd. 10" B.Oak N02°W 136.65'

USFS Survey Lat 44°36'57" 34856

Long 84°15'03" 39669



Signed by, Marvin E. Myers

Date July 28, 1995

Surveyor's Michigan License No. 31600