

SURVEY & REMONUMENTATION

SEP 29 1994

COMMISSION

For corners in

Oscoda (County)

Located in:

Corner Code ~~44~~

1. Public Land Survey

T 26N R 2E

C-12

2. Property Controlling

in Section

8

3. Miscellaneous

Property in Sec.

6

4. Lot No. _____, Recorded Plat

4. Lot No. _____, Recorded Plat

5. Private Claims

5. Private Claims

I, Marvin E. Myers, in a field survey on July 7, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO-July 1839 Coon
Mon-Post
WIT: 4" Spruce Pine N39 $\frac{1}{2}$ W 17 lks.
6" Spruce Pine S54 $\frac{1}{2}$ E 27 lks.

GLO-Oct. 1935 Guy Veal
Mon-3 $\frac{1}{2}$ " Brass Tablet in 6" Conc.
WIT: J. Pine N09°E 41 lks.
J. Pine S76 $\frac{1}{2}$ °W 47 lks.

April 1911 C.O. Seeley
Mon-Set Post

(no evidence of corner, set by proportionate distance)

L.2, pg.133 1969 N.Caldwell
Mon-Fd. US GLO Mon
WIT: C N-S Road East 62.30'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 6" Concrete Monument with 3½" Brass Tablet. Verified position by measurement to accessories of record and accepted as a careful and faithful re-establishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon-6" Conc. Mon with 3½" Brass Tablet placed ½"x18" steel rebar along N. side for magnetic attraction
 Will: Set Nail in N. side of USFS location post West 0.59'
 Set Nail in W. side 5" Poplar North 14.25'
 Set Nail in SE side 6" J. Pine N45°E 7.65'
 Set Nail in E. side 5" B. Oak South 6.38'
 4 N-S asphalt road 64.00'

APPROVED

**County Remuneration
Peer Review Group**

Signed by

Date July 24, 1974

Surveyor's Michigan License No. 31600

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 19
REVISED MAY 14, 19
REVISED JAN. 19

L3 Pg 277

STATE OF MICHIGAN
OSCEOLA COUNTY
FILED

14 SEP 94 11:07 A.M.

PATSY J. PETERS
REGISTER OF DEEDS

Register of Deeds Stamp & File Number