

REMONUMENTATION SURVEY &

SEP 29 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oscoda
(County)

Located In:

Corner Code=##

- | | | T | 26N | R | 2E | E - 9 |
|------------------------------------|---|---|-----|---|----|-------|
| 1. Public Land Survey | | T | | R | | |
| | | T | | R | | |
| | | T | | R | | |
| | | T | | R | | |
| 2. Property Controlling in Section | S | T | | R | | |
| | S | T | | R | | |
| 3. Miscellaneous | S | T | | R | | |
| Property in Sec. | S | T | | R | | |

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Marvin E. Myers, in a field survey on July 8, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:

GLO-July 1839 Coon	GLO 1935 Guy Veal
Mon-Post	Mon-Fd. 1" Pipe
WIT: 12" Aspen S09°E 22 lks.	Replaced with
10" Aspen N14°W 15 lks.	WIT: E-W Road Sou


1964 N. Caldwell
Mon-Fd. US GLO Mon.
No accessories available

- B Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

Monument found US GLO Monument and accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon-US. GLO 6" Dia. Conc. Mon. with 3 1/2" Dia. Brass. Tablet with 1" Pipe. 0.6'. South of corner for magnetic attraction
WIT: Set 4" Polebarn Nail in West side 7" Apple Tree N30°E 40.60'
Fd. face of USFS location post N08°E 33.00'
Face of Power Pole S52°E 67.30'
Set 4" Polebarn Nail SW side Fence Post N37°W 46.04'



Signed by Marvin E. Meyer Date Aug-23-1994