

SURVEY &
REMONUMENTATION

SEP 29 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oscoda (County)

Located In:

Corner Code ##

1. Public Land Survey

T 26N R 2E

E - 10

2. Property Controlling

S

T

R

E - 10

3. Miscellaneous

S

T

R

E - 10

Property in Sec.

S

T

R

E - 10

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Marvin E. Myers, in a field survey on July 8, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, re-monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO-July 1839 Coon

Mon-Post

WIT: 10" Spruce Pine N47°W 8 lks.

14" Spruce Pine S37°E 24 lks.

April 1911 C.O. Seeley

Mon-Post

WIT: NBT 8" Spruce N27°W 18½ lks.

May 1934 G.D. Henning

Mon-Angle iron

WIT: NBT 4" J. Pine N22°E 1.42½ chs.

NBT 14" Norway S65°W 1.56 chs.

GLO-1935 Guy Veal

Mon-3½" Dia. Brass Tablet in

6"x24" Conc. Mon.

WIT: 8" B.Oak S17 3/4°E 138 lks.

In Fence N-S

2 lks. N. of 3"x3" Post

Apparently local cor.

July 1964 N. Caldwell

Mon-US GLO

LCRC L.2, pg.130 Apr. 1969 N. Caldwell

Mon-US GLO Mon in C. E-W roadway with fences N-S

WIT: 14" J. Pine N25°W 37.55'

Power Pole N30°E 54.60'

LCRC L.1, pg.37 Dec. 1972 N. Caldwell

Mon-US GLO MON in E-W Road on N-S fence

WIT: 14" J. Pine N25°W 37.55'

Power Pole N30°E 54.60'

Corner Fence Post South 23.40'

L/L, pg. 400 Nov. 1973 N. Caldwell

Mon-Fd. GLO Conc. Mon.

WIT: Fence Cor. South 24.00'

½" Bar & Cap south 33.00'

Fence Cor. North 24.00'

¾" Bar & Cap North 33.00'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.

Found US GLO 6" Concrete Monument with 3½" Brass Tablet. Verified position by measurements to accessories of record and is accepted as a careful and faithful reestablishment of the position of the original corner.

NOTE: April 1911 Seeley reestablished corner position by proportionate measurement; May 1934 G. Henning found and perpetuated the same with angle iron; 1935 Guy Veal did not accept the Henning corner and reestablished the corner position by proportionate measurement.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon-US GLO 6" Concrete Monument with 3½" Brass Tablet

WIT: Fd. Steel Fence Post along South edge of mon. 0.40' for magnetic attraction

Fd. Power Pole N30°E 54.65'

Fd. Corner Fence Post South 23.40'

Set 4" Polebarn Nail in top center of Telephone Pedestal Support Post N25°E 26.50'

Face of Steel Satellite Antenna Post N40°W 83.65'

Set 4" Polebarn Nail NW side 4" J. Pine S45°W 45.85'

Face of USFS location Post South 26.70'

APPROVED

County Remonumentation

Peer Review Group

Signed by Marvin E. Myers

Date

Aug 23, 1994

Surveyor's Michigan License No. 31600

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1993

