

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74. MICH. P.A.1970

FOR CORNERS OF-- LOCATED IN-- CORNER CODE NUMBER

1. PUBLIC LAND SURVEY 18 T. 13 N. R. 10 W. B-5 N $\frac{1}{2}$, C-5 N $\frac{1}{2}$ Cor.

2. PROPERTY CONTROLLING IN SECTION _____, T. _____, S., R. _____, E. W. C-6 E $\frac{1}{2}$ Cor.,

3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, S., R. _____, E. W. B-7 S $\frac{1}{2}$ Cor.

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

1978 JAN 25 PM 5 59

STATE OF MICHIGAN
COUNTY OF Kalamazoo
REGISTERED FOR RECORD

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Gerald J. Gray do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram-over) were, in a field survey on Jan. 3, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-5 N $\frac{1}{2}$ Cor.

Set R.R. Spike on straight line
Prorated G.L.O.
Dist. N.E. Cor. to N.W. Cor.

C-6 E $\frac{1}{2}$ Cor.

Set R.R. Spike E Rd., Split Dist.
N.E. to S.E. Corners

C-5 N.E. Cor.

Set $\frac{1}{2}$ " ϕ Rod based on
existing occupation

B-6 C $\frac{1}{2}$ Cor.

Set $\frac{1}{2}$ " ϕ Rod at Int. of E-W & N-S $\frac{1}{4}$ lines

B-7 S $\frac{1}{2}$ Cor.

Fnd. Tile & Conc. Mon. set by CO. PO. CO.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-5 N $\frac{1}{2}$ Cor.

R.R. Spike
14" Oak N55°E 56.7'
34" Maple N30°W 34.9'
14" Oak N70°W 83.00'

C-5 N.E. Cor.

$\frac{1}{2}$ " ϕ Rod
18" Oak N10°E 120.80'
24" Oak S15°E 61.63'
Ut. Pole S50°W 39.48'
12" Oak S55°W 114.33'

C-6 E $\frac{1}{2}$ Cor.

R.R. Spike
Tel. Pole S30°E 60.0'
14" Oak N35°W 39.2'
16" Oak N15°W 92.5'

B-6 C $\frac{1}{2}$ Cor.

13" Beech North 12.53'
12" Oak East 53.30'
16" Oak S30°W 55.15'

B-7 S $\frac{1}{2}$ Cor.

Tile & Conc.
16" Oak S60°W 41.00'
14" Oak N60°W 32.35'
14" Oak N55°E 55.6'

SIGNED BY Gerald J. Gray

DATE Jan. 25, 1978

SURVEYOR'S MICHIGAN REGISTRATION NO. 17741

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ CHIEF OF SURVEY PARTY

DATE _____


APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR

DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Form No. ML 1978
BOSTON, MASS. & CO., CAMBRIDGE, MASS.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS



LIBR 1 PAGE 386