

2013 PRESQUE ISLE COUNTY, STATE OF MICHIGAN REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

Instrument  
201300004596 OR  
Liber Page  
544 879

For corners in Presque Isle (County) Located in: \_\_\_\_\_ Corner Code # \_\_\_\_\_

- Public Land Survey  
T 33N R 5E Corner Code # C-11  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_
- Property Controlling in S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
Section S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
- Miscellaneous S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
Property in Sec. S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

201300004596  
Filed for Record in  
PRESQUE ISLE COUNTY  
CATHY I. IDALSKI, REGISTER OF DEEDS  
12-10-2013 At 03:49 pm.  
LC-REMON 17.00  
OR Liber 544 Page 879 - 880

Register of Deeds Stamp & Figure Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Travis L. Horrocks, in a field survey on MARCH 27, 2013 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-11  
SEE BACK

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-11  
FOUND 1/2" ROD & CAP #15410  
"T" POST FENCE GOING EAST, OTHER FE IN AREA LAYING DOWN  
NORTH TO SOUTH BANK 0.50 CHAIN (33") MEASURED 31.5"  
EAST TO EAST BANK 1.44 CHAIN (93.06") MEASURED 96.0"  
N 09° E 24.63' 10" MAPLE IN CLUMP W/BLAZE  
S 33° E 16.09' 30" TWIN MAPLE W/BLAZE BEING FE COR  
S 48° W 36.05' STUMP MOUND

atified by Peer Group  
in accordance with P.A. 345

Chairman Travis L. Horrocks

Date 9-19-2013

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11  
1/2" ROD & REMON CAP #59298  
"T" POST FENCE GOING EAST  
N 09° E 24.63' 10" MAPLE IN CLUMP W/BLAZE (OW)  
S 33° E 16.09' 30" TWIN MAPLE W/BLAZE BEING FE COR (OW) #59298  
N 86° E 42.40' 15" MAPLE #59298  
N 45° W 6.76' 11" MAPLE #59298

Signed by Travis L. Horrocks  
Surveyor's Michigan License No. 59298

WITNESS TAGS & NAILS USED

Date 09/23/13



A	B	C	D	E	F	G	H	I	J	K	L	M
1	2	3	4	5	6	7	8	9	10	11	12	13
14	15	16	17	18	19	20	21	22	23	24	25	26
27	28	29	30	31	32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47	48	49	50	51	52