

**SURVEY &
REMONUMENTATION**

Montmorency County Remonumentation

APR 24 1995

**LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners of a **COMMISSION**

Montmorency (County)	Located In: Montmorency Township	Corner Code -# A-4
1. Public Land Survey	T <u>32</u> N R <u>3</u> E	<u>A-4</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

STATE OF MICHIGAN
MONTMORENCY COUNTY
Recorded & Filed
11-10-1994 14:14:28
A. PANGAN-MCELROY
REGISTER OF DEEDS

**APPROVED BY
PEER GROUP**

AUG 05 94

Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

A	B	C	D	E	F	G	H	I	J	K	L
2	6	5	4	3	2	1					
3											
4	7	8	9	10	11	12					
5											
6	18	17	16	15	14	13					
7											
8	19	20	21	22	23	24					
9											
10	30	29	28	27	26	25					
11											
12	31	32	33	34	35	36					
13											

I, Don Marlatt, in a field survey on November 8, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:


- (A-4) W. 1/4 Cor. Sec. 7, T 32 N, R 3 E
Original post set by Hiram Burnham July, 1850 in South edge of marsh.
Corner matches Call. (Beech Post).
12" Aspen S 80° W 16 links
12" Aspen N 62° W 28 links
Schaaf - DNR - No Date.
D. Porter - Recorded Act 74, L. 1, P. 397 on July 22, 1987.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (A-4) W. 1/4 Cor. Sec. 7, T 32 N, R 3 E
Found 2" pipe in concrete.
10" Maple N 34° W 22.14'
10" Tr. Maple S 68° E 7.9'
8" Maple S 13° W 14.27'
8" Maple S 63° W 24.78'
Hunting wire corner N 55° W 34'
No evidence of original corner.
Accepted as a perpetuation of the original government corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- (A-4) W. 1/4 Cor. Sec. 7, T 32 N, R 3 E
Left 2" pipe in concrete in place.
Placed Remonumentation Cap.
10" Maple N 34° W 22.18'
8" Maple S 63° W 24.88'
8" Maple S 13° W 14.27'
10" Tr. Maple S 68° E 7.90'
Witnesses marked with a 30 penny spike & I.D. tag #18660.



Signed by Donald E. Marlatt Date 11-9-1994

Surveyor's Michigan License No. 18660