

CHEBOYGAN COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

CHEBOYGAN
(County)

Located In:

Corner Code #

1. Public Land Survey

38N 2W
T 37NR 2W

C-13
C-1

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

RECEIVED FOR RECORD

at 11:21 O'Clock 12-18-9 A.M.

Joanne Spray

CLERK/REGISTER
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, JAMES H. GRANGER, in a field survey on JULY 15, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-1 1840 Original Survey
John Mullett

36" Pine Corner

1972 Survey
Orlando Doyle #7319

Metal Monument

1977 LCRC
Orlando Doyle #7319

Concrete Monument

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6	5			4		3		2		1	
3													
4		7	8			9		10		11		12	
5													
6		18	17			16		15		14		13	
7													
8		19	20			21		22		23		24	
9													
10		30	29			28		27		26		25	
11													
12		31	32			33		34		35		36	
13													



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-1 Found concrete monument and 2 existing witnesses grown over. Set remonumentation cap on concrete monument.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-1 Concrete Monument with Remonumentation Cap
16" Poplar N19°W 86.42' Set tag #16041
PP N19°E 115.65' Set tag #16041
24" Maple S62°E 18.41' Set tag #16041
PP S57°W 48.08' Fd tag #41099

LIBER 011 PAGE 25

Signed by


James H. Granger

Date

Nov. 17, 1997

Surveyor's Michigan

License No. 16041



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 25, 1971
REVISED 14, 1976

REVISED JAN. 1993
REVISED OCT. 1996