

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Paul R. Bressette
For corner(s) in: Delta County

Field Survey Date: 03/22/2017 , 03/23/2017

Original Public Land Survey Corner				Corner Code
S		T	R	
S		T	R	
S		T	R	
S		T	R	
Protracted Public Land Survey Corner				Corner Code
S	9	T	41N R 24W	11
S		T	R	
S	9	T	41N R 24W	12
S		T	R	

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13	A	B	C	D	E	F	G	H	I	J	K	L	M	13

Part A. Corner History

(11) Southwest One-sixteenth corner of Section 9. Found 5/8" capped iron pin "TS Wanic PS 44296".

(12) South One-sixteenth corner of Section 9. Found 5/8" capped iron pin "TS Wanic PS 44296".

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

(11) Found capped iron pin falls 0.21' from calculated position. Witnessed capped iron as found.

(12) Found capped iron pin falls 0.10' from calculated position. Witnessed capped iron as found.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(11) 5/8" iron pin w/ plastic cap
08" Spruce N89E 6.1' (BT)
10" Tamarack S63E 13.7' (1/16S,BT)
05" Tamarack S23W 18.2' (1/16S,BT)
04" Tamarack N51W 41.5' (1/16S,BT)
All trees are blazed, scribed and painted.
Measurements are to nail in side of tree, bearings are magnetic.

(12) 5/8" iron pin w/ plastic cap
06" Spruce N81E 8.45' (BT)
06" Spruce S17E 10.35' (1/16S,BT)
08" Tamarack S38W 11.1' (1/16S,BT)
10" Tamarack N29W 18.15' (1/16S,BT)
All trees are blazed, scribed and painted.
Measurements are to nail in side of tree, bearings are magnetic.

Certifying Surveyor's Name Paul R. Bressette
Professional Surveyor's License No.: 37270

Date

Prepared By: Paul R. Bressette, PS Michigan Dept. of Natural Resources, 410 W. M35 Gwinn, MI 49841